

Lekcija 6 - Nizovi

Pregled

- 6.1 Uvod
- 6.2 Nizovi
- 6.3 Deklaracija niza
- 6.4 Primjeri upotrebe nizova
- 6.5 Nizovi kao argumenti funkcije
- 6.6 Sortiranje niza
- 6.7 Primjer: izračunavanje srednje vrijednosti, medijane i moda
- 6.8 Traženje u nizu
- 6.9 Višedimenzionalni nizovi

Ciljevi lekcije

- U ovoj lekciji:
 - Uvešćete nizove kao strukture podataka.
 - Shvatićete kako se nizovi koriste za čuvanje, sortiranje i pretraživanje liste vrijednosti.
 - Razumijećete kako se definiše i inicijalizuje niz i kako se pristupa elementima niza.
 - Naučićete kako se niz predaje kao argument funkcije.
 - Shvatićete osnovne tehnike sortiranja.
 - Upotrebljavaćete višedimenzionalne nizove.

6.1 Uvod

- Nizovi (arrays)
 - Strukture povezanih podataka istog tipa
 - Statički entiteti – iste veličine kroz čitav program
 - Dinamičke strukture obrađujemo kasnije


6.2 Nizovi

Ime niza(Svi
elementi imaju isto
ime c)

- Niz
 - Grupa uzastopnih memorijskih lokacija
 - Imaju isto ime i tip
- Pristup elementu
 - Ime niza
 - Indeks (poziciju)
- Format:

arrayname[position number]

 - Prvi element ima indeks 0
 - n-to elementni niz c:
 - `c[0], c[1]...c[n - 1]`



c[0]	-45
c[1]	6
c[2]	0
c[3]	72
c[4]	1543
c[5]	-89
c[6]	0
c[7]	62
c[8]	-3
c[9]	1
c[10]	6453
c[11]	78

Pozicija unutar
niza c (indeks)

6.2 Nizovi

- Elementi niza ponašaju se kao obične promjenljive

```
c[ 0 ] = 3;  
printf( "%d", c[ 0 ] );
```

- Moguće je izvoditi operacije sa indeksima. Ako x ima vrijednost 3, tada je

```
c[ 5 - 2 ] == c[ 3 ] == c[ x ]
```

6.2 Nizovi

Operatori						Asocijativnost	Tip
[]	()					left to right	highest
++	--	!	(type)			right to left	unary
*	/	%				left to right	multiplicative
+	-					left to right	additive
<	<=	>	>=			left to right	relational
==	!=					left to right	equality
&&						left to right	logical and
						left to right	logical or
? :						right to left	conditional
=	+=	-=	*=	/=	%=	right to left	assignment
,						left to right	comma

Fig. 6.2 Prioritet operatora.

6.3 Definisanje niza

- Definisanje niza

- Zadajemo ime

- Tip elemenata

- Broj elemenata

- `arrayType arrayName[numberOfElements];`

- Primjeri:

- `int c[10];`

- `float myArray[3284];`

- Definisanje više nizova istog tipa

- Format sličan regularnim promjenljivim

- Primjer:

- `int b[100], x[27];`

6.4 Primjeri upotrebe nizova

- Inicijalizacija

```
int n[ 5 ] = { 1, 2, 3, 4, 5 };
```

- Ako nema dovoljno elemenata ostali se inicijalizuju nulama

```
int n[ 5 ] = { 0 }
```

- Svi elementi su 0
- Ako ih je previše, sintaksna greška
- C nizovi nemaju provjeru granica

- Ako veličina niza nije data, sama se odredi iz inicijalizatora

```
int n[ ] = { 1, 2, 3, 4, 5 };
```

- 5 inicijalizatora, pa niz ima 5 elemenata

**fig06_03.c**

```
1  /* Fig. 6.3: fig06_03.c
2     initializing an array */
3  #include <stdio.h>
4
5  /* function main begins program execution */
6  int main()
7  {
8     int n[ 10 ]; /* n is an array of 10 integers */
9     int i;       /* counter */
10
11     /* initialize elements of array n to 0 */
12     for ( i = 0; i < 10; i++ ) {
13         n[ i ] = 0; /* set element at location i to 0 */
14     } /* end for */
15
16     printf( "%s%13s\n", "Element", "Value" );
17
18     /* output contents of array n in tabular format */
19     for ( i = 0; i < 10; i++ ) {
20         printf( "%7d%13d\n", i, n[ i ] );
21     } /* end for */
22
23     return 0; /* indicates successful termination */
24
25 } /* end main */
```

Element	Value
0	0
1	0
2	0
3	0
4	0
5	0
6	0
7	0
8	0
9	0



Outline

Program Output

6.4 Primjeri upotrebe nizova

- Nizovi karaktera
 - String `"first"` je statički niz karaktera
 - Nizovi karaktera se mogu inicijalizovati pomoću literala

```
char string1[] = "first";
```

 - Null karakter `'\0'` označava kraj stringa
 - `string1` u stvari ima 6 elemenata
 - Što je ekvivalentno sa

```
char string1[] = { 'f', 'i', 'r', 's', 't', '\0' };
```
 - Možemo pristupati pojedinačnim karakterima

```
string1[3]
```

 je karakter `'s'`
 - Ime niza je adresa niza, pa `&` nije potrebno u `scanf`

```
scanf( "%s", string2 );
```

 - Čita karaktere do pojave bjeline (whitespace)
 - Može pisati i iza kraja niza (budite oprezni)



```
1  /* Fig. 6.4: fig06_04.c
2      Initializing an array with an initializer list */
3  #include <stdio.h>
4
5  /* function main begins program execution */
6  int main()
7  {
8      /* use initializer list to initialize array n */
9      int n[ 10 ] = { 32, 27, 64, 18, 95, 14, 90, 70, 60, 37 };
10     int i; /* counter */
11
12     printf( "%s%13s\n", "Element", "Value" );
13
14     /* output contents of array in tabular format */
15     for ( i = 0; i < 10; i++ ) {
16         printf( "%7d%13d\n", i, n[ i ] );
17     } /* end for */
18
19     return 0; /* indicates successful termination */
20
21 } /* end main */
```

[Outline](#)**Program Output**

Element	Value
0	32
1	27
2	64
3	18
4	95
5	14
6	90
7	70
8	60
9	37



fig06_05.c

```
1  /* Fig. 6.5: fig06_05.c
2      Initialize the elements of array s to the even integers from 2 to 20 */
3  #include <stdio.h>
4  #define SIZE 10
5
6  /* function main begins program execution */
7  int main()
8  {
9      /* symbolic constant SIZE can be used to specify array size */
10     int s[ SIZE ]; /* array s has 10 elements */
11     int j;          /* counter */
12
13     for ( j = 0; j < SIZE; j++ ) { /* set the values */
14         s[ j ] = 2 + 2 * j;
15     } /* end for */
16
17     printf( "%s%13s\n", "Element", "Value" );
18
19     /* output contents of array s in tabular format */
20     for ( j = 0; j < SIZE; j++ ) {
21         printf( "%7d%13d\n", j, s[ j ] );
22     } /* end for */
23
24     return 0; /* indicates successful termination */
25
26 } /* end main */
```

[Outline](#)**Program Output**

Element	Value
0	2
1	4
2	6
3	8
4	10
5	12
6	14
7	16
8	18
9	20



fig06_06.c

```
1  /* Fig. 6.6: fig06_06.c
2      Compute the sum of the elements of the array */
3  #include <stdio.h>
4  #define SIZE 12
5
6  /* function main begins program execution */
7  int main()
8  {
9      /* use initializer list to initialize array */
10     int a[ SIZE ] = { 1, 3, 5, 4, 7, 2, 99, 16, 45, 67, 89, 45 };
11     int i;          /* counter */
12     int total = 0; /* sum of array */
13
14     /* sum contents of array a */
15     for ( i = 0; i < SIZE; i++ ) {
16         total += a[ i ];
17     } /* end for */
18
19     printf( "Total of array element values is %d\n", total );
20
21     return 0; /* indicates successful termination */
22
23 } /* end main */
```

Program Output

Total of array element values is 383



Outline

fig06_07.c (Part 1 of 2)

```
1  /* Fig. 6.7: fig06_07.c
2      Student poll program */
3  #include <stdio.h>
4  #define RESPONSE_SIZE 40 /* define array sizes */
5  #define FREQUENCY_SIZE 11
6
7  /* function main begins program execution */
8  int main()
9  {
10     int answer; /* counter */
11     int rating; /* counter */
12
13     /* initialize frequency counters to 0 */
14     int frequency[ FREQUENCY_SIZE ] = { 0 };
15
16     /* place survey responses in array responses */
17     int responses[ RESPONSE_SIZE ] = { 1, 2, 6, 4, 8, 5, 9, 7, 8, 10,
18         1, 6, 3, 8, 6, 10, 3, 8, 2, 7, 6, 5, 7, 6, 8, 6, 7, 5, 6, 6,
19         5, 6, 7, 5, 6, 4, 8, 6, 8, 10 };
20
```



Outline

fig06_07.c (Part 2 of 2)

```

21  /* for each answer, select value of an element of array responses
22      and use that value as subscript in array frequency to
23      determine element to increment */
24  for ( answer = 0; answer < RESPONSE_SIZE; answer++ ) {
25      ++frequency[ responses [ answer ] ];
26  } /* end for */
27
28  /* display results */
29  printf( "%s%17s\n", "Rating", "Frequency" );
30
31  /* output frequencies in tabular format */
32  for ( rating = 1; rating < FREQUENCY_SIZE; rating++ ) {
33      printf( "%6d%17d\n", rating, frequency[ rating ] );
34  } /* end for */
35
36  return 0; /* indicates successful termination */
37
38 } /* end main */

```

Rating	Frequency
1	2
2	2
3	2
4	2
5	5
6	11
7	5
8	7
9	1
10	3

Program Output

**fig06_08.c (Part 1 of 2)**

```
1  /* Fig. 6.8: fig06_08.c
2      Histogram printing program */
3  #include <stdio.h>
4  #define SIZE 10
5
6  /* function main begins program execution */
7  int main()
8  {
9      /* use initializer list to initialize array n */
10     int n[ SIZE ] = { 19, 3, 15, 7, 11, 9, 13, 5, 17, 1 };
11     int i; /* outer counter */
12     int j; /* inner counter */
13
14     printf( "%s%13s%17s\n", "Element", "Value", "Histogram" );
15
16     /* for each element of array n, output a bar in histogram */
17     for ( i = 0; i < SIZE; i++ ) {
18         printf( "%7d%13d", i, n[ i ] );
19
20         for ( j = 1; j <= n[ i ]; j++ ) { /* print one bar */
21             printf( "%c", '*' );
22         } /* end inner for */
23     }
```



Outline



fig06_08.c (Part 2 of 2)

Program Output

```

24     printf( "\\n" ); /* start next line of output */
25 } /* end outer for */
26
27     return 0; /* indicates successful termination */
28
29 } /* end main */

```

Element	Value	Histogram
0	19	*****
1	3	***
2	15	*****
3	7	*****
4	11	*****
5	9	*****
6	13	*****
7	5	*****
8	17	*****
9	1	*



Outline

fig06_09.c (Part 1 of 2)

```
1  /* Fig. 6.9: fig06_09.c
2      Roll a six-sided die 6000 times */
3  #include <stdio.h>
4  #include <stdlib.h>
5  #include <time.h>
6  #define SIZE 7
7
8  /* function main begins program execution */
9  int main()
10 {
11     int face;                /* random number with value 1 - 6 */
12     int roll;                /* roll counter */
13     int frequency[ SIZE ] = { 0 }; /* initialize array to 0 */
14
15     srand( time( NULL ) ); /* seed random-number generator */
16
17     /* roll die 6000 times */
18     for ( roll = 1; roll <= 6000; roll++ ) {
19         face = rand() % 6 + 1;
20         ++frequency[ face ]; /* replaces 26-line switch of Fig. 5.8 */
21     } /* end for */
22
23     printf( "%s%17s\n", "Face", "Frequency" );
24
```



Outline



fig06_09.c (Part 2 of 2)

Program Output

```
25  /* output frequency elements 1-6 in tabular format */
26  for ( face = 1; face < SIZE; face++ ) {
27      printf( "%4d%17d\n", face, frequency[ face ] );
28  } /* end for */
29
30  return 0; /* indicates successful termination */
31
32 } /* end main */
```

Face	Frequency
1	1029
2	951
3	987
4	1033
5	1010
6	990



Outline

fig06_10.c (Part 1 of 2)

```
1  /* Fig. 6.10: fig06_10.c
2     Treating character arrays as strings */
3  #include <stdio.h>
4
5  /* function main begins program execution */
6  int main()
7  {
8      char string1[ 20 ];           /* reserves 20 characters */
9      char string2[] = "string literal"; /* reserves 15 characters */
10     int i;                        /* counter */
11
12     /* read string from user into array string2 */
13     printf("Enter a string: ");
14     scanf( "%s", string1 );
15
16     /* output strings */
17     printf( "string1 is: %s\nstring2 is: %s\n"
18            "string1 with spaces between characters is:\n",
19            string1, string2 );
20
21     /* output characters until null character is reached */
22     for ( i = 0; string1[ i ] != '\0'; i++ ) {
23         printf( "%c ", string1[ i ] );
24     } /* end for */
25
```

```
26     printf( "\\n" );  
27  
28     return 0; /* indicates successful termination */  
29  
30 } /* end main */
```

```
Enter a string: Hello there  
string1 is: Hello  
string2 is: string literal  
string1 with spaces between characters is:  
H e l l o
```



Outline



**fig06_10.c (Part 2
of 2)**

**fig06_11.c (Part 1
of 3)**

```
1  /* Fig. 6.11: fig06_11.c
2     Static arrays are initialized to zero */
3  #include <stdio.h>
4
5  void staticArrayInit( void );    /* function prototype */
6  void automaticArrayInit( void ); /* function prototype */
7
8  /* function main begins program execution */
9  int main()
10 {
11     printf( "First call to each function:\n" );
12     staticArrayInit();
13     automaticArrayInit();
14
15     printf( "\n\nSecond call to each function:\n" );
16     staticArrayInit();
17     automaticArrayInit();
18
19     return 0; /* indicates successful termination */
20
21 } /* end main */
22
```



Outline

fig06_11.c (Part 2
of 3)

```
23 /* function to demonstrate a static local array */
24 void staticArrayInit( void )
25 {
26     /* initializes elements to 0 first time function is called */
27     static int array1[ 3 ];
28     int i; /* counter */
29
30     printf( "\nValues on entering staticArrayInit:\n" );
31
32     /* output contents of array1 */
33     for ( i = 0; i <= 2; i++ ) {
34         printf( "array1[ %d ] = %d  ", i, array1[ i ] );
35     } /* end for */
36
37     printf( "\nValues on exiting staticArrayInit:\n" );
38
39     /* modify and output contents of array1 */
40     for ( i = 0; i <= 2; i++ ) {
41         printf( "array1[ %d ] = %d  ", i, array1[ i ] += 5 );
42     } /* end for */
43
44 } /* end function staticArrayInit */
45
```



Outline

fig06_11.c (Part 3 of 3)

```
46 /* function to demonstrate an automatic local array */
47 void automaticArrayInit( void )
48 {
49     /* initializes elements each time function is called */
50     int array2[ 3 ] = { 1, 2, 3 };
51     int i; /* counter */
52
53     printf( "\n\nValues on entering automaticArrayInit:\n" );
54
55     /* output contents of array2 */
56     for ( i = 0; i <= 2; i++ ) {
57         printf("array2[ %d ] = %d  ", i, array2[ i ] );
58     } /* end for */
59
60     printf( "\nValues on exiting automaticArrayInit:\n" );
61
62     /* modify and output contents of array2 */
63     for ( i = 0; i <= 2; i++ ) {
64         printf( "array2[ %d ] = %d  ", i, array2[ i ] += 5 );
65     } /* end for */
66
67 } /* end function automaticArrayInit */
```



First call to each function:

Values on entering staticArrayInit:

array1[0] = 0 array1[1] = 0 array1[2] = 0

Values on exiting staticArrayInit:

array1[0] = 5 array1[1] = 5 array1[2] = 5

Values on entering automaticArrayInit:

array2[0] = 1 array2[1] = 2 array2[2] = 3

Values on exiting automaticArrayInit:

array2[0] = 6 array2[1] = 7 array2[2] = 8

Second call to each function:

Values on entering staticArrayInit:

array1[0] = 5 array1[1] = 5 array1[2] = 5

Values on exiting staticArrayInit:

array1[0] = 10 array1[1] = 10 array1[2] = 10

Values on entering automaticArrayInit:

array2[0] = 1 array2[1] = 2 array2[2] = 3

Values on exiting automaticArrayInit:

array2[0] = 6 array2[1] = 7 array2[2] = 8

6.5 Nizovi kao argumenti funkcije

- Predaja argumenata
 - Niz se predaje kao argument funkcije tako što se preda ime niza bez “uglastih” zagrada

```
int myArray[ 24 ];  
myFunction( myArray, 24 );
```
 - Veličina niza se obično predaje kao drugi argument
 - Nizovi se predaju po referenci
 - Ime niza je adresa prvog elementa
 - Funkcija zna gdje je niz smješten u memoriji
 - Mijenja se originalna memorijska lokacija
- Elementi niza kao argumenti
 - Predaju se po vrijednosti
 - Predaje se kao obična promjenljiva (na primjer, `myArray[3]`)

6.5 Nizovi kao argumenti funkcije

- Prototip funkcije

```
void modifyArray( int b[], int arraySize );
```

- Imena argumenata su opcionalna u prototipu

- `int b[]` možemo zapisati kao `int []`

- `int arraySize` možemo zapisati kao `int`



Outline

fig06_12.c

```
1  /* Fig. 6.12: fig06_12.c
2      The name of an array is the same as &array[ 0 ] */
3  #include <stdio.h>
4
5  /* function main begins program execution */
6  int main()
7  {
8      char array[ 5 ]; /* define an array of size 5 */
9
10     printf( "    array = %p\n&array[0] = %p\n"
11         "    &array = %p\n",
12         array, &array[ 0 ], &array );
13
14     return 0; /* indicates successful termination */
15
16 } /* end main */
```

```
    array = 0012FF78
&array[0] = 0012FF78
&array    = 0012FF78
```

Program Output



Outline

fig06_13.c (Part 1 of 3)

```
1  /* Fig. 6.13: fig06_13.c
2      Passing arrays and individual array elements to functions */
3  #include <stdio.h>
4  #define SIZE 5
5
6  /* function prototypes */
7  void modifyArray( int b[], int size );
8  void modifyElement( int e );
9
10 /* function main begins program execution */
11 int main()
12 {
13     int a[ SIZE ] = { 0, 1, 2, 3, 4 }; /* initialize a */
14     int i; /* counter */
15
16     printf( "Effects of passing entire array by reference:\n\nThe "
17            "values of the original array are:\n" );
18
19     /* output original array */
20     for ( i = 0; i < SIZE; i++ ) {
21         printf( "%3d", a[ i ] );
22     } /* end for */
23
24     printf( "\n" );
25
```


**fig06_13.c (Part 2 of 3)**

```
26  /* pass array a to modifyArray by reference */
27  modifyArray( a, SIZE );
28
29  printf( "The values of the modified array are:\n" );
30
31  /* output modified array */
32  for ( i = 0; i < SIZE; i++ ) {
33      printf( "%3d", a[ i ] );
34  } /* end for */
35
36  /* output value of a[ 3 ] */
37  printf( "\n\nEffects of passing array element "
38          "by value:\n\nThe value of a[3] is %d\n", a[ 3 ] );
39
40  modifyElement( a[ 3 ] ); /* pass array element a[ 3 ] by value */
41
42  /* output value of a[ 3 ] */
43  printf( "The value of a[ 3 ] is %d\n", a[ 3 ] );
44
45  return 0; /* indicates successful termination */
46
47 } /* end main */
48
```



fig06_13.c (Part 3 of 3)

```
49  /* in function modifyArray, "b" points to the original array "a"
50     in memory */
51  void modifyArray( int b[], int size )
52  {
53     int j; /* counter */
54
55     /* multiply each array element by 2 */
56     for ( j = 0; j < size; j++ ) {
57         b[ j ] *= 2;
58     } /* end for */
59
60 } /* end function modifyArray */
61
62 /* in function modifyElement, "e" is a local copy of array element
63    a[ 3 ] passed from main */
64 void modifyElement( int e )
65 {
66     /* multiply parameter by 2 */
67     printf( "Value in modifyElement is %d\n", e *= 2 );
68 } /* end function modifyElement */
```



Effects of passing entire array by reference:

The values of the original array are:

0 1 2 3 4

The values of the modified array are:

0 2 4 6 8

Effects of passing array element by value:

The value of a[3] is 6

Value in modifyElement is 12

The value of a[3] is 6

**fig06_14.c (Part 1 of 2)**

```
1  /* Fig. 6.14: fig06_14.c
2     Demonstrating the const type qualifier with arrays */
3  #include <stdio.h>
4
5  void tryToModifyArray( const int b[] ); /* function prototype */
6
7  /* function main begins program execution */
8  int main()
9  {
10     int a[] = { 10, 20, 30 }; /* initialize a */
11
12     tryToModifyArray( a );
13
14     printf("%d %d %d\n", a[ 0 ], a[ 1 ], a[ 2 ] );
15
16     return 0; /* indicates successful termination */
17
18 } /* end main */
19
```



Outline



fig06_14.c (Part 2 of 2)

Program Output

```
20 /* in function tryToModifyArray, array b is const, so it cannot be
21    used to modify the original array a in main. */
22 void tryToModifyArray( const int b[] )
23 {
24     b[ 0 ] /= 2;    /* error */
25     b[ 1 ] /= 2;    /* error */
26     b[ 2 ] /= 2;    /* error */
27 } /* end function tryToModifyArray */
```

Compiling...

FIG06_14.C

fig06_14.c(24) : error C2166: l-value specifies const object

fig06_14.c(25) : error C2166: l-value specifies const object

fig06_14.c(26) : error C2166: l-value specifies const object

6.6 Sortiranje niza

- Sortiranje podataka
 - Skoro svaka organizacija mora da sortira neke podatke
- “Bubble sort” (sinking sort)
 - Više prolazaka kroz niz
 - Uzastopni parovi elemenata se porede
 - Ako su već u rastućem redosledu, ništa se ne mijenja
 - Ako je opadajući redosled, elementi zamijene mjesta
 - Ponavljamo postupak
- Primjer:
 - original: 3 4 2 6 7
 - prolaz 1: 3 2 4 6 7
 - prolaz 2: 2 3 4 6 7
 - Mali elementi isplivavaju (“bubble”) na vrh



Outline

fig06_15.c (Part 1 of 3)

```
1  /* Fig. 6.15: fig06_15.c
2      This program sorts an array's values into ascending order */
3  #include <stdio.h>
4  #define SIZE 10
5
6  /* function main begins program execution */
7  int main()
8  {
9      /* initialize a */
10     int a[ SIZE ] = { 2, 6, 4, 8, 10, 12, 89, 68, 45, 37 };
11     int i;    /* inner counter */
12     int pass; /* outer counter */
13     int hold; /* temporary location used to swap array elements */
14
15     printf( "Data items in original order\n" );
16
17     /* output original array */
18     for ( i = 0; i < SIZE; i++ ) {
19         printf( "%4d", a[ i ] );
20     } /* end for */
21
```

**fig06_15.c (Part 2 of 3)**

```
22  /* bubble sort */
23  /* loop to control number of passes */
24  for ( pass = 1; pass < SIZE; pass++ ) {
25
26      /* loop to control number of comparisons per pass */
27      for ( i = 0; i < SIZE - 1; i++ ) {
28
29          /* compare adjacent elements and swap them if first
30           element is greater than second element */
31          if ( a[ i ] > a[ i + 1 ] ) {
32              hold = a[ i ];
33              a[ i ] = a[ i + 1 ];
34              a[ i + 1 ] = hold;
35          } /* end if */
36
37      } /* end inner for */
38
39  } /* end outer for */
40
41  printf( "\nData items in ascending order\n" );
42
```




Outline



fig06_15.c (Part 3 of 3)

Program Output

```
43      /* output sorted array */
44      for ( i = 0; i < SIZE; i++ ) {
45          printf( "%4d", a[ i ] );
46      } /* end for */
47
48      printf( "\n" );
49
50      return 0; /* indicates successful termination */
51
```

Data items in original order

2 6 4 8 10 12 89 68 45 37

Data items in ascending order

2 4 6 8 10 12 37 45 68 89

6.7 Primjer: izračunavanje srednje vrijednosti, medijane i moda

- Srednja vrijednost (mean , average)
- Medijana – broj u sredini sortirane liste
 - 1, 2, 3, 4, 5
 - 3 je medijana
- Mode – broj koji se najčešće pojavljuje
 - 1, 1, 1, 2, 3, 3, 4, 5
 - 1 je mod



Outline

fig06_16.c (Part 1 of 8)

```
1  /* Fig. 6.16: fig06_16.c
2      This program introduces the topic of survey data analysis.
3      It computes the mean, median, and mode of the data */
4  #include <stdio.h>
5  #define SIZE 99
6
7  /* function prototypes */
8  void mean( const int answer[] );
9  void median( int answer[] );
10 void mode( int freq[], const int answer[] ) ;
11 void bubbleSort( int a[] );
12 void printArray( const int a[] );
13
14 /* function main begins program execution */
15 int main()
16 {
17     int frequency[ 10 ] = { 0 }; /* initialize array frequency */
18
```

**fig06_16.c (Part 2
of 8)**

```
19  /* initialize array response */
20  int response[ SIZE ] =
21      { 6, 7, 8, 9, 8, 7, 8, 9, 8, 9,
22        7, 8, 9, 5, 9, 8, 7, 8, 7, 8,
23        6, 7, 8, 9, 3, 9, 8, 7, 8, 7,
24        7, 8, 9, 8, 9, 8, 9, 7, 8, 9,
25        6, 7, 8, 7, 8, 7, 9, 8, 9, 2,
26        7, 8, 9, 8, 9, 8, 9, 7, 5, 3,
27        5, 6, 7, 2, 5, 3, 9, 4, 6, 4,
28        7, 8, 9, 6, 8, 7, 8, 9, 7, 8,
29        7, 4, 4, 2, 5, 3, 8, 7, 5, 6,
30        4, 5, 6, 1, 6, 5, 7, 8, 7 };
31
32  /* process responses */
33  mean( response );
34  median( response );
35  mode( frequency, response );
36
37  return 0; /* indicates successful termination */
38
39 } /* end main */
40
```

**fig06_16.c (Part 3
of 8)**

```
41 /* calculate average of all response values */
42 void mean( const int answer[] )
43 {
44     int j;          /* counter */
45     int total = 0; /* variable to hold sum of array elements */
46
47     printf( "%s\n%s\n%s\n", "*****", "  Mean", "*****" );
48
49     /* total response values */
50     for ( j = 0; j < SIZE; j++ ) {
51         total += answer[ j ];
52     } /* end for */
53
54     printf( "The mean is the average value of the data\n"
55            "items. The mean is equal to the total of\n"
56            "all the data items divided by the number\n"
57            "of data items ( %d ). The mean value for\n"
58            "this run is: %d / %d = %.4f\n\n",
59            SIZE, total, SIZE, ( double ) total / SIZE );
60 } /* end function mean */
61
```



Outline

fig06_16.c (Part 4
of 8)

```
62 /* sort array and determine median element's value */
63 void median( int answer[] )
64 {
65     printf( "\n%s\n%s\n%s\n%s",
66             "*****", " Median", "*****",
67             "The unsorted array of responses is" );
68
69     printArray( answer ); /* output unsorted array */
70
71     bubbleSort( answer ); /* sort array */
72
73     printf( "\n\nThe sorted array is" );
74     printArray( answer ); /* output sorted array */
75
76     /* display median element */
77     printf( "\n\nThe median is element %d of\n"
78             "the sorted %d element array.\n"
79             "For this run the median is %d\n\n",
80             SIZE / 2, SIZE, answer[ SIZE / 2 ] );
81 } /* end function median */
82
```

**fig06_16.c (Part 5
of 8)**

```
83  /* determine most frequent response */
84  void mode( int freq[], const int answer[] )
85  {
86      int rating;          /* counter */
87      int j;               /* counter */
88      int h;               /* counter */
89      int largest = 0;     /* represents largest frequency */
90      int modeValue = 0;   /* represents most frequent response */
91
92      printf( "\n%s\n%s\n%s\n",
93              "*****", "  Mode", "*****" );
94
95      /* initialize frequencies to 0 */
96      for ( rating = 1; rating <= 9; rating++ ) {
97          freq[ rating ] = 0;
98      } /* end for */
99
100     /* summarize frequencies */
101     for ( j = 0; j < SIZE; j++ ) {
102         ++freq[ answer[ j ] ];
103     } /* end for */
104
```



Outline

fig06_16.c (Part 6 of 8)

```
105  /* output headers for result columns */
106  printf( "%s%11s%19s\n\n%54s\n%54s\n\n",
107          "Response", "Frequency", "Histogram",
108          "1    1    2    2", "5    0    5    0    5" );
109
110  /* output results */
111  for ( rating = 1; rating <= 9; rating++ ) {
112      printf( "%8d%11d", rating, freq[ rating ] );
113
114      /* keep track of mode value and largest frequency value */
115      if ( freq[ rating ] > largest ) {
116          largest = freq[ rating ];
117          modeValue = rating;
118      } /* end if */
119
120      /* output histogram bar representing frequency value */
121      for ( h = 1; h <= freq[ rating ]; h++ ) {
122          printf( "*" );
123      } /* end inner for */
124
125      printf( "\n" ); /* being new line of output */
126  } /* end outer for */
127
```


**fig06_16.c (Part 7
of 8)**

```
128  /* display the mode value */
129  printf( "The mode is the most frequent value.\n"
130          "For this run the mode is %d which occurred"
131          " %d times.\n", modeValue, largest );
132} /* end function mode */
133
134/* function that sorts an array with bubble sort algorithm */
135void bubbleSort( int a[] )
136{
137    int pass; /* counter */
138    int j;     /* counter */
139    int hold;  /* temporary location used to swap elements */
140
141    /* loop to control number of passes */
142    for ( pass = 1; pass < SIZE; pass++ ) {
143
144        /* loop to control number of comparisons per pass */
145        for ( j = 0; j < SIZE - 1; j++ ) {
146
147            /* swap elements if out of order */
148            if ( a[ j ] > a[ j + 1 ] ) {
149                hold = a[ j ];
150                a[ j ] = a[ j + 1 ];
151                a[ j + 1 ] = hold;
152            } /* end if */
153        }
```

**fig06_16.c (Part 8
of 8)**

```
154     } /* end inner for */
155
156 } /* end outer for */
157
158 } /* end function bubbleSort */
159
160 /* output array contents (20 values per row) */
161 void printArray( const int a[] )
162 {
163     int j; /* counter */
164
165     /* output array contents */
166     for ( j = 0; j < SIZE; j++ ) {
167
168         if ( j % 20 == 0 ) { /* begin new line every 20 values */
169             printf( "\n" );
170         } /* end if */
171
172         printf( "%2d", a[ j ] );
173     } /* end for */
174
175 } /* end function printArray */
```



Program Output

Mean

The mean is the average value of the data items. The mean is equal to the total of all the data items divided by the number of data items (99). The mean value for this run is: $681 / 99 = 6.8788$

Median

The unsorted array of responses is

```
6 7 8 9 8 7 8 9 8 9 7 8 9 5 9 8 7 8 7 8
6 7 8 9 3 9 8 7 8 7 7 8 9 8 9 8 9 7 8 9
6 7 8 7 8 7 9 8 9 2 7 8 9 8 9 8 9 7 5 3
5 6 7 2 5 3 9 4 6 4 7 8 9 6 8 7 8 9 7 8
7 4 4 2 5 3 8 7 5 6 4 5 6 1 6 5 7 8 7
```

The sorted array is

```
1 2 2 2 3 3 3 3 4 4 4 4 4 5 5 5 5 5 5 5
5 6 6 6 6 6 6 6 6 6 7 7 7 7 7 7 7 7 7 7
7 7 7 7 7 7 7 7 7 7 7 7 8 8 8 8 8 8 8 8
8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9
```



Program Output (continued)

The median is element 49 of
the sorted 99 element array.
For this run the median is 7

Mode

Response	Frequency	Histogram
		<div> <div></div> <div>1</div> <div>1</div> <div>2</div> <div>2</div> </div> <div> <div>5</div> <div>0</div> <div>5</div> <div>0</div> <div>5</div> </div>
1	1	*
2	3	***
3	4	****
4	5	*****
5	8	*****
6	9	*****
7	23	*****
8	27	*****
9	19	*****

The mode is the most frequent value.

For this run the mode is 8 which occurred 27 times.

6.8 Traženje u nizu: linearno i binarno

- Binarno traženje
 - Samo za sortirane nizove
 - Upoređujemo `middle` element sa `key`
 - Ako su jednaki, traženje završava uspješno (match found)
 - Ako je `key < middle`, posmatramo prvu polovinu niza
 - Ako je `key > middle`, posmatramo drugu polovinu niza
 - Ponavljamo postupak
 - Veoma brzo pretraživanje; najviše n koraka, gdje je n najmanji prirodan broj takav da je 2^n veće od broja elemenata
 - Za niz od 30 elemenata potrebno je najviše 5 koraka, jer je
 - $2^5 > 30$

**fig06_18.c (Part 1
of 3)**

```
1  /* Fig. 6.18: fig06_18.c
2     Linear search of an array */
3  #include <stdio.h>
4  #define SIZE 100
5
6  /* function prototype */
7  int linearSearch( const int array[], int key, int size );
8
9  /* function main begins program execution */
10 int main()
11 {
12     int a[ SIZE ]; /* create array a */
13     int x;          /* counter */
14     int searchKey; /* value to locate in a */
15     int element;    /* variable to hold location of searchKey or -1 */
16
17     /* create data */
18     for ( x = 0; x < SIZE; x++ ) {
19         a[ x ] = 2 * x;
20     } /* end for */
21
22     printf( "Enter integer search key:\n" );
23     scanf( "%d", &searchKey );
24
```



Outline

fig06_18.c (Part 2 of 3)

```
25  /* attempt to locate searchKey in array a */
26  element = linearSearch( a, searchKey, SIZE );
27
28  /* display results */
29  if ( element != -1 ) {
30      printf( "Found value in element %d\n", element );
31  } /* end if */
32  else {
33      printf( "Value not found\n" );
34  } /* end else */
35
36  return 0; /* indicates successful termination */
37
38 } /* end main */
39
40 /* compare key to every element of array until the location is found
41    or until the end of array is reached; return subscript of element
42    if key or -1 if key is not found */
43 int linearSearch( const int array[], int key, int size )
44 {
45     int n; /* counter */
46
47     /* loop through array */
48     for ( n = 0; n < size; ++n ) {
49
```



Outline



fig06_18.c (Part 3
of 3)

Program Output

```
50     if ( array[ n ] == key ) {  
51         return n; /* return location of key */  
52     } /* end if */  
53  
54 } /* end for */  
55  
56 return -1; /* key not found */  
57  
58 } /* end function linearSearch */
```

```
Enter integer search key:  
36  
Found value in element 18
```

```
Enter integer search key:  
37  
Value not found
```




fig06_19.c (Part 1 of 5)

```
1  /* Fig. 6.19: fig06_19.c
2      Binary search of an array */
3  #include <stdio.h>
4  #define SIZE 15
5
6  /* function prototypes */
7  int binarySearch( const int b[], int searchKey, int low, int high );
8  void printHeader( void );
9  void printRow( const int b[], int low, int mid, int high );
10
11 /* function main begins program execution */
12 int main()
13 {
14     int a[ SIZE ]; /* create array a */
15     int i;         /* counter */
16     int key;       /* value to locate in array a */
17     int result;    /* variable to hold location of key or -1 */
18
19     /* create data */
20     for ( i = 0; i < SIZE; i++ ) {
21         a[ i ] = 2 * i;
22     } /* end for */
23
24     printf( "Enter a number between 0 and 28: " );
25     scanf( "%d", &key );
26
```

**fig06_19.c (Part 2 of 5)**

```
27  printHeader();
28
29  /* search for key in array a */
30  result = binarySearch( a, key, 0, SIZE - 1 );
31
32  /* display results */
33  if ( result != -1 ) {
34      printf( "\n%d found in array element %d\n", key, result );
35  } /* end if */
36  else {
37      printf( "\n%d not found\n", key );
38  } /* end else */
39
40  return 0; /* indicates successful termination */
41
42 } /* end main */
43
44 /* function to perform binary search of an array */
45 int binarySearch( const int b[], int searchKey, int low, int high )
46 {
47     int middle; /* variable to hold middle element of array */
48
```

**fig06_19.c (Part 3
of 5)**

```
49  /* loop until low subscript is greater than high subscript */
50  while ( low <= high ) {
51
52      /* determine middle element of subarray being searched */
53      middle = ( low + high ) / 2;
54
55      /* display subarray used in this loop iteration */
56      printRow( b, low, middle, high );
57
58      /* if searchKey matched middle element, return middle */
59      if ( searchKey == b[ middle ] ) {
60          return middle;
61      } /* end if */
62
63      /* if searchKey less than middle element, set new high */
64      else if ( searchKey < b[ middle ] ) {
65          high = middle - 1; /* search low end of array */
66      } /* end else if */
67
68      /* if searchKey greater than middle element, set new low */
69      else {
70          low = middle + 1; /* search high end of array */
71      } /* end else */
72
73  } /* end while */
74
```

**fig06_19.c (Part 4
of 5)**

```
75     return -1;    /* searchKey not found */
76
77 } /* end function binarySearch */
78
79 /* Print a header for the output */
80 void printHeader( void )
81 {
82     int i; /* counter */
83
84     printf( "\nSubscripts:\n" );
85
86     /* output column head */
87     for ( i = 0; i < SIZE; i++ ) {
88         printf( "%3d ", i );
89     } /* end for */
90
91     printf( "\n" ); /* start new line of output */
92
93     /* output line of - characters */
94     for ( i = 1; i <= 4 * SIZE; i++ ) {
95         printf( "-" );
96     } /* end for */
97
98     printf( "\n" ); /* start new line of output */
99 } /* end function printHeader */
100
```

**fig06_19.c (Part 5
of 5)**

```
101/* Print one row of output showing the current
102   part of the array being processed. */
103void printRow( const int b[], int low, int mid, int high )
104{
105   int i; /* counter */
106
107   /* loop through entire array */
108   for ( i = 0; i < SIZE; i++ ) {
109
110       /* display spaces if outside current subarray range */
111       if ( i < low || i > high ) {
112           printf( "    " );
113       } /* end if */
114       else if ( i == mid ) { /* display middle element */
115           printf( "%3d*", b[ i ] ); /* mark middle value */
116       } /* end else if */
117       else { /* display other elements in subarray */
118           printf( "%3d ", b[ i ] );
119       } /* end else */
120
121   } /* end for */
122
123   printf( "\n" ); /* start new line of output */
124} /* end function printRow */
```



Program Output

Enter a number between 0 and 28: 25

Subscripts:

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
0	2	4	6	8	10	12	14*	16	18	20	22	24	26	28
								16	18	20	22*	24	26	28
												24	26*	28
												24*		

25 not found

Enter a number between 0 and 28: 8

Subscripts:

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
0	2	4	6	8	10	12	14*	16	18	20	22	24	26	28
0	2	4	6*	8	10	12								
				8	10*	12								
				8*										

8 found in array element 4



Program Output (continued)

Enter a number between 0 and 28: 6

Subscripts:

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
---	---	---	---	---	---	---	---	---	---	----	----	----	----	----

0	2	4	6	8	10	12	14*	16	18	20	22	24	26	28
---	---	---	---	---	----	----	-----	----	----	----	----	----	----	----

0	2	4	6*	8	10	12
---	---	---	----	---	----	----

6 found in array element 3

6.9 Višedimenzionalni nizovi

- Višedimenzionalni nizovi
 - 2D nizovi – tabele sa redovima i kolonama (m×n array)
 - Matrice

	Column 0	Column 1	Column 2	Column 3
Row 0	a[0][0]	a[0][1]	a[0][2]	a[0][3]
Row 1	a[1][0]	a[1][1]	a[1][2]	a[1][3]
Row 2	a[2][0]	a[2][1]	a[2][2]	a[2][3]

Ime niza Indeks reda Indeks kolone

6.9 Višedimenzioni nizovi

- Inicijalizacija

- `int b[2][2] = { { 1, 2 }, { 3, 4 } };`
- Inicijalizatori grupisani u redove pomoću zagrada
- Ako ih nema dovoljno, nespecificirani elementi su nule

1	2
3	4

`int b[2][2] = { { 1 }, { 3, 4 } };`

1	0
3	4

- Pristupanje elementu

- Zadajemo prvo red pa kolonu
`printf("%d", b[0][1]);`

**fig06_21.c (Part 1
of 2)**

```
1  /* Fig. 6.21: fig06_21.c
2      Initializing multidimensional arrays */
3  #include <stdio.h>
4
5  void printArray( const int a[][ 3 ] ); /* function prototype */
6
7  /* function main begins program execution */
8  int main()
9  {
10     /* initialize array1, array2, array3 */
11     int array1[ 2 ][ 3 ] = { { 1, 2, 3 }, { 4, 5, 6 } };
12     int array2[ 2 ][ 3 ] = { 1, 2, 3, 4, 5 };
13     int array3[ 2 ][ 3 ] = { { 1, 2 }, { 4 } };
14
15     printf( "Values in array1 by row are:\n" );
16     printArray( array1 );
17
18     printf( "Values in array2 by row are:\n" );
19     printArray( array2 );
20
21     printf( "Values in array3 by row are:\n" );
22     printArray( array3 );
23
24     return 0; /* indicates successful termination */
25
26 } /* end main */
27
```



Outline

fig06_21.c (Part 2
of 2)

```
28 /* function to output array with two rows and three columns */
29 void printArray( const int a[][ 3 ] )
30 {
31     int i; /* counter */
32     int j; /* counter */
33
34     /* loop through rows */
35     for ( i = 0; i <= 1; i++ ) {
36
37         /* output column values */
38         for ( j = 0; j <= 2; j++ ) {
39             printf( "%d ", a[ i ][ j ] );
40         } /* end inner for */
41
42         printf( "\n" ); /* start new line of output */
43     } /* end outer for */
44
45 } /* end function printArray */
```

```
Values in array1 by row are:
1 2 3
4 5 6
Values in array2 by row are:
1 2 3
4 5 0
Values in array3 by row are:
1 2 0
4 0 0
```

Program Output



Outline

fig06_22.c (Part 1 of 6)

```
1  /* Fig. 6.22: fig06_22.c
2      Double-subscripted array example */
3  #include <stdio.h>
4  #define STUDENTS 3
5  #define EXAMS 4
6
7  /* function prototypes */
8  int minimum( const int grades[][ EXAMS ], int pupils, int tests );
9  int maximum( const int grades[][ EXAMS ], int pupils, int tests );
10 double average( const int setOfGrades[], int tests );
11 void printArray( const int grades[][ EXAMS ], int pupils, int tests );
12
13 /* function main begins program execution */
14 int main()
15 {
16     int student; /* counter */
17
18     /* initialize student grades for three students (rows) */
19     const int studentGrades[ STUDENTS ][ EXAMS ] =
20         { { 77, 68, 86, 73 },
21           { 96, 87, 89, 78 },
22           { 70, 90, 86, 81 } };
23
```



Outline

fig06_22.c (Part 2
of 6)

```
24  /* output array studentGrades */
25  printf( "The array is:\n" );
26  printArray( studentGrades, STUDENTS, EXAMS );
27
28  /* determine smallest and largest grade values */
29  printf( "\n\nLowest grade: %d\nHighest grade: %d\n",
30          minimum( studentGrades, STUDENTS, EXAMS ),
31          maximum( studentGrades, STUDENTS, EXAMS ) );
32
33  /* calculate average grade for each student */
34  for ( student = 0; student <= STUDENTS - 1; student++ ) {
35      printf( "The average grade for student %d is %.2f\n",
36              student, average( studentGrades[ student ], EXAMS ) );
37  } /* end for */
38
39  return 0; /* indicates successful termination */
40
41 } /* end main */
42
43 /* Find the minimum grade */
44 int minimum( const int grades[][ EXAMS ], int pupils, int tests )
45 {
46     int i;           /* counter */
47     int j;           /* counter */
48     int lowGrade = 100; /* initialize to highest possible grade */
49
```



fig06_22.c (Part 3 of 6)

```
50  /* loop through rows of grades */
51  for ( i = 0; i < pupils; i++ ) {
52
53      /* loop through columns of grades */
54      for ( j = 0; j < tests; j++ ) {
55
56          if ( grades[ i ][ j ] < lowGrade ) {
57              lowGrade = grades[ i ][ j ];
58          } /* end if */
59
60      } /* end inner for */
61
62  } /* end outer for */
63
64  return lowGrade; /* return minimum grade */
65
66 } /* end function minimum */
67
68 /* Find the maximum grade */
69 int maximum( const int grades[][ EXAMS ], int pupils, int tests )
70 {
71     int i;           /* counter */
72     int j;           /* counter */
73     int highGrade = 0; /* initialize to lowest possible grade */
74
```



Outline

fig06_22.c (Part 4
of 6)

```
75  /* loop through rows of grades */
76  for ( i = 0; i < pupils; i++ ) {
77
78      /* loop through columns of grades */
79      for ( j = 0; j < tests; j++ ) {
80
81          if ( grades[ i ][ j ] > highGrade ) {
82              highGrade = grades[ i ][ j ];
83          } /* end if */
84
85      } /* end inner for */
86
87  } /* end outer for */
88
89  return highGrade; /* return maximum grade */
90
91 } /* end function maximum */
92
93 /* Determine the average grade for a particular student */
94 double average( const int setOfGrades[], int tests )
95 {
96     int i;          /* counter */
97     int total = 0; /* sum of test grades */
98
```



Outline

fig06_22.c (Part 5
of 6)

```
99      /* total all grades for one student */
100     for ( i = 0; i < tests; i++ ) {
101         total += setOfGrades[ i ];
102     } /* end for */
103
104     return ( double ) total / tests; /* average */
105
106 } /* end function average */
107
108 /* Print the array */
109 void printArray( const int grades[][ EXAMS ], int pupils, int tests )
110 {
111     int i; /* counter */
112     int j; /* counter */
113
114     /* output column heads */
115     printf( "                [0]  [1]  [2]  [3]" );
116
117     /* output grades in tabular format */
118     for ( i = 0; i < pupils; i++ ) {
119
120         /* output label for row */
121         printf( "\nstudentGrades[%d] ", i );
122
```




fig06_22.c (Part 6 of 6)

```
123      /* output grades for one student */
124      for ( j = 0; j < tests; j++ ) {
125          printf( "%-5d", grades[ i ][ j ] );
126      } /* end inner for */
127
128  } /* end outer for */
129
130} /* end function printArray */
```

The array is:

	[0]	[1]	[2]	[3]
studentGrades[0]	77	68	86	73
studentGrades[1]	96	87	89	78
studentGrades[2]	70	90	86	81

Lowest grade: 68

Highest grade: 96

The average grade for student 0 is 76.00

The average grade for student 1 is 87.50

The average grade for student 2 is 81.75