

15.4 Sorting

Sorting of data plays an important role in database systems for two reasons. First, SQL queries can specify that the output be sorted. Second, and equally important for query processing, several of the relational operations, such as joins, can be implemented efficiently if the input relations are first sorted. Thus, we discuss sorting here before discussing the join operation in Section 15.5.

We can sort a relation by building an index on the sort key and then using that index to read the relation in sorted order. However, such a process orders the relation only *logically*, through an index, rather than *physically*. Hence, the reading of tuples in the sorted order may lead to a disk access (disk seek plus block transfer) for each record, which can be very expensive, since the number of records can be much larger than the number of blocks. For this reason, it may be desirable to order the records physically.

The problem of sorting has been studied extensively, both for relations that fit entirely in main memory and for relations that are bigger than memory. In the first case, standard sorting techniques such as quick-sort can be used. Here, we discuss how to handle the second case.

15.4.1 External Sort-Merge Algorithm

Sorting of relations that do not fit in memory is called **external sorting**. The most commonly used technique for external sorting is the **external sort-merge** algorithm. We describe the external sort-merge algorithm next. Let M denote the number of blocks in the main memory buffer available for sorting, that is, the number of disk blocks whose contents can be buffered in available main memory.

1. In the first stage, a number of sorted **runs** are created; each run is sorted but contains only some of the records of the relation.

```

 $i = 0$ ;
repeat
    read  $M$  blocks of the relation, or the rest of the relation,
        whichever is smaller;
    sort the in-memory part of the relation;
    write the sorted data to run file  $R_i$ ;
     $i = i + 1$ ;
until the end of the relation
  
```

2. In the second stage, the runs are *merged*. Suppose, for now, that the total number of runs, N , is less than M , so that we can allocate one block to each run and have space left to hold one block of output. The merge stage operates as follows:

```

read one block of each of the  $N$  files  $R_i$  into a buffer block in memory;
repeat
    choose the first tuple (in sort order) among all buffer blocks;
    write the tuple to the output, and delete it from the buffer block;
    if the buffer block of any run  $R_i$  is empty and not end-of-file( $R_i$ )
        then read the next block of  $R_i$  into the buffer block;
until all input buffer blocks are empty

```

The output of the merge stage is the sorted relation. The output file is buffered to reduce the number of disk write operations. The preceding merge operation is a generalization of the two-way merge used by the standard in-memory sort-merge algorithm; it merges N runs, so it is called an **N-way merge**.

In general, if the relation is much larger than memory, there may be M or more runs generated in the first stage, and it is not possible to allocate a block for each run during the merge stage. In this case, the merge operation proceeds in multiple passes. Since there is enough memory for $M - 1$ input buffer blocks, each merge can take $M - 1$ runs as input.

The initial *pass* functions in this way: It merges the first $M - 1$ runs (as described in item 2 above) to get a single run for the next pass. Then, it merges the next $M - 1$ runs similarly, and so on, until it has processed all the initial runs. At this point, the number of runs has been reduced by a factor of $M - 1$. If this reduced number of runs is still greater than or equal to M , another pass is made, with the runs created by the first pass as input. Each pass reduces the number of runs by a factor of $M - 1$. The passes repeat as many times as required, until the number of runs is less than M ; a final pass then generates the sorted output.

Figure 15.4 illustrates the steps of the external sort-merge for an example relation. For illustration purposes, we assume that only one tuple fits in a block ($f_r = 1$), and we assume that memory holds at most three blocks. During the merge stage, two blocks are used for input and one for output.

15.4.2 Cost Analysis of External Sort-Merge

We compute the disk-access cost for the external sort-merge in this way: Let b_r denote the number of blocks containing records of relation r . The first stage reads every block of the relation and writes them out again, giving a total of $2b_r$ block transfers. The initial number of runs is $\lceil b_r/M \rceil$. During the merge pass, reading in each run one block at a time leads to a large number of seeks; to reduce the number of seeks, a larger number of blocks, denoted b_b , are read or written at a time, requiring b_b buffer blocks to be allocated to each input run and to the output run. Then, $\lfloor M/b_b \rfloor - 1$ runs can be merged in each merge pass, decreasing the number of runs by a factor of $\lfloor M/b_b \rfloor - 1$. The total number of merge passes required is $\lceil \log_{\lfloor M/b_b \rfloor - 1} (b_r/M) \rceil$. Each of these passes reads every block of the relation once and writes it out once, with two exceptions. First, the final pass can produce the sorted output without writing its result




Figure 15.4 External sorting using sort-merge.

to disk. Second, there may be runs that are not read in or written out during a pass—for example, if there are $\lfloor M/b_b \rfloor$ runs to be merged in a pass, $\lfloor M/b_b \rfloor - 1$ are read in and merged, and one run is not accessed during the pass. Ignoring the (relatively small) savings due to the latter effect, the total number of block transfers for external sorting of the relation is:

$$b_r(2\lceil \log_{\lfloor M/b_b \rfloor - 1}(b_r/M) \rceil + 1)$$

Applying this equation to the example in Figure 15.4, with b_b set to 1, we get a total of $12 * (4 + 1) = 60$ block transfers, as you can verify from the figure. Note that these above numbers do not include the cost of writing out the final result.

We also need to add the disk-seek costs. Run generation requires seeks for reading data for each of the runs as well as for writing the runs. Each merge pass requires around $\lceil b_r/b_b \rceil$ seeks for reading data.⁶ Although the output is written sequentially, if it is on the same disk as the input runs, the head may have moved away between writes of consecutive blocks. Thus we would have to add a total of $2\lceil b_r/b_b \rceil$ seeks for each merge pass, except the final pass (since we assume the final result is not written back to disk).

⁶To be more precise, since we read each run separately and may get fewer than b_b blocks when reading the end of a run, we may require an extra seek for each run. We ignore this detail for simplicity.

$$2\lceil b_r/M \rceil + \lceil b_r/b_b \rceil (2\lceil \log_{\lfloor M/b_b \rfloor - 1} (b_r/M) \rceil - 1)$$

Applying this equation to the example in Figure 15.4, we get a total of $8 + 12 * (2 * 2 - 1) = 44$ disk seeks if we set the number of buffer blocks per run b_b to 1.

15.5 Join Operation

In this section, we study several algorithms for computing the join of relations, and we analyze their respective costs.

We use the term **equi-join** to refer to a join of the form $r \bowtie_{r.A=s.B} s$, where A and B are attributes or sets of attributes of relations r and s , respectively.

We use as a running example the expression:

$$student \bowtie takes$$

using the same relation schemas that we used in Chapter 2. We assume the following information about the two relations:

- Number of records of *student*: $n_{student} = 5000$.
- Number of blocks of *student*: $b_{student} = 100$.
- Number of records of *takes*: $n_{takes} = 10,000$.
- Number of blocks of *takes*: $b_{takes} = 400$.

15.5.1 Nested-Loop Join

Figure 15.5 shows a simple algorithm to compute the theta join, $r \bowtie_{\theta} s$, of two relations r and s . This algorithm is called the **nested-loop join** algorithm, since it basically consists of a pair of nested **for** loops. Relation r is called the **outer relation** and relation s the **inner relation** of the join, since the loop for r encloses the loop for s . The algorithm uses the notation $t_r \cdot t_s$, where t_r and t_s are tuples; $t_r \cdot t_s$ denotes the tuple constructed by concatenating the attribute values of tuples t_r and t_s .

Like the linear file-scan algorithm for selection, the nested-loop join algorithm requires no indices, and it can be used regardless of what the join condition is. Extending the algorithm to compute the natural join is straightforward, since the natural join can be expressed as a theta join followed by elimination of repeated attributes by a projection. The only change required is an extra step of deleting repeated attributes from the tuple $t_r \cdot t_s$, before adding it to the result.

The nested-loop join algorithm is expensive, since it examines every pair of tuples in the two relations. Consider the cost of the nested-loop join algorithm. The number of pairs of tuples to be considered is $n_r * n_s$, where n_r denotes the number of tuples in r , and n_s denotes the number of tuples in s . For each record in r , we have to perform

```

for each tuple  $t_r$  in  $r$  do begin
  for each tuple  $t_s$  in  $s$  do begin
    test pair  $(t_r, t_s)$  to see if they satisfy the join condition  $\theta$ 
    if they do, add  $t_r \cdot t_s$  to the result;
  end
end

```

Figure 15.5 Nested-loop join.

a complete scan on s . In the worst case, the buffer can hold only one block of each relation, and a total of $n_r * b_s + b_r$ block transfers would be required, where b_r and b_s denote the number of blocks containing tuples of r and s , respectively. We need only one seek for each scan on the inner relation s since it is read sequentially, and a total of b_r seeks to read r , leading to a total of $n_r + b_r$ seeks. In the best case, there is enough space for both relations to fit simultaneously in memory, so each block would have to be read only once; hence, only $b_r + b_s$ block transfers would be required, along with two seeks.

If one of the relations fits entirely in main memory, it is beneficial to use that relation as the inner relation, since the inner relation would then be read only once. Therefore, if s is small enough to fit in main memory, our strategy requires only a total $b_r + b_s$ block transfers and two seeks—the same cost as that for the case where both relations fit in memory.

Now consider the natural join of *student* and *takes*. Assume for now that we have no indices whatsoever on either relation, and that we are not willing to create any index. We can use the nested loops to compute the join; assume that *student* is the outer relation and *takes* is the inner relation in the join. We will have to examine $5000 * 10,000 = 50 * 10^6$ pairs of tuples. In the worst case, the number of block transfers is $5000 * 400 + 100 = 2,000,100$, plus $5000 + 100 = 5100$ seeks. In the best-case scenario, however, we can read both relations only once and perform the computation. This computation requires at most $100 + 400 = 500$ block transfers, plus two seeks—a significant improvement over the worst-case scenario. If we had used *takes* as the relation for the outer loop and *student* for the inner loop, the worst-case cost of our final strategy would have been $10,000 * 100 + 400 = 1,000,400$ block transfers, plus 10,400 disk seeks. The number of block transfers is significantly less, and although the number of seeks is higher, the overall cost is reduced, assuming $t_S = 4$ milliseconds and $t_T = 0.1$ milliseconds.

15.5.2 Block Nested-Loop Join

If the buffer is too small to hold either relation entirely in memory, we can still obtain a major saving in block accesses if we process the relations on a per-block basis, rather

than on a per-tuple basis. Figure 15.6 shows **block nested-loop join**, which is a variant of the nested-loop join where every block of the inner relation is paired with every block of the outer relation. Within each pair of blocks, every tuple in one block is paired with every tuple in the other block, to generate all pairs of tuples. As before, all pairs of tuples that satisfy the join condition are added to the result.

The primary difference in cost between the block nested-loop join and the basic nested-loop join is that, in the worst case, each block in the inner relation s is read only once for each *block* in the outer relation, instead of once for each *tuple* in the outer relation. Thus, in the worst case, there will be a total of $b_r * b_s + b_r$ block transfers, where b_r and b_s denote the number of blocks containing records of r and s , respectively. Each scan of the inner relation requires one seek, and the scan of the outer relation requires one seek per block, leading to a total of $2 * b_r$ seeks. It is more efficient to use the smaller relation as the outer relation, in case neither of the relations fits in memory. In the best case, where the inner relation fits in memory, there will be $b_r + b_s$ block transfers and just two seeks (we would choose the smaller relation as the inner relation in this case).

Now return to our example of computing $student \bowtie takes$, using the block nested-loop join algorithm. In the worst case, we have to read each block of *takes* once for each block of *student*. Thus, in the worst case, a total of $100 * 400 + 100 = 40,100$ block transfers plus $2 * 100 = 200$ seeks are required. This cost is a significant improvement over the $5000 * 400 + 100 = 2,000,100$ block transfers plus 5100 seeks needed in the worst case for the basic nested-loop join. The best-case cost remains the same—namely, $100 + 400 = 500$ block transfers and two seeks.

The performance of the nested-loop and block nested-loop procedures can be further improved:

```

for each block  $B_r$  of  $r$  do begin
  for each block  $B_s$  of  $s$  do begin
    for each tuple  $t_r$  in  $B_r$  do begin
      for each tuple  $t_s$  in  $B_s$  do begin
        test pair  $(t_r, t_s)$  to see if they satisfy the join condition
        if they do, add  $t_r \cdot t_s$  to the result;
      end
    end
  end
end

```

Figure 15.6 Block nested-loop join.

- If the join attributes in a natural join or an equi-join form a key on the inner relation, then for each outer relation tuple the inner loop can terminate as soon as the first match is found.
- In the block nested-loop algorithm, instead of using disk blocks as the blocking unit for the outer relation, we can use the biggest size that can fit in memory, while leaving enough space for the buffers of the inner relation and the output. In other words, if memory has M blocks, we read in $M - 2$ blocks of the outer relation at a time, and when we read each block of the inner relation we join it with all the $M - 2$ blocks of the outer relation. This change reduces the number of scans of the inner relation from b_r to $\lceil b_r / (M - 2) \rceil$, where b_r is the number of blocks of the outer relation. The total cost is then $\lceil b_r / (M - 2) \rceil * b_s + b_r$ block transfers and $2\lceil b_r / (M - 2) \rceil$ seeks.
- We can scan the inner loop alternately forward and backward. This scanning method orders the requests for disk blocks so that the data remaining in the buffer from the previous scan can be reused, thus reducing the number of disk accesses needed.
- If an index is available on the inner loop's join attribute, we can replace file scans with more efficient index lookups. Section 15.5.3 describes this optimization.

15.5.3 Indexed Nested-Loop Join

In a nested-loop join (Figure 15.5), if an index is available on the inner loop's join attribute, index lookups can replace file scans. For each tuple t_r in the outer relation r , the index is used to look up tuples in s that will satisfy the join condition with tuple t_r .

This join method is called an **indexed nested-loop join**; it can be used with existing indices, as well as with temporary indices created for the sole purpose of evaluating the join.

Looking up tuples in s that will satisfy the join conditions with a given tuple t_r is essentially a selection on s . For example, consider *student* \bowtie *takes*. Suppose that we have a *student* tuple with *ID* “00128”. Then, the relevant tuples in *takes* are those that satisfy the selection “*ID* = 00128”.

The cost of an indexed nested-loop join can be computed as follows: For each tuple in the outer relation r , a lookup is performed on the index for s , and the relevant tuples are retrieved. In the worst case, there is space in the buffer for only one block of r and one block of the index. Then, b_r I/O operations are needed to read relation r , where b_r denotes the number of blocks containing records of r ; each I/O requires a seek and a block transfer, since the disk head may have moved in between each I/O. For each tuple in r , we perform an index lookup on s . Then, the cost of the join can be computed as $b_r(t_T + t_S) + n_r * c$, where n_r is the number of records in relation r , and c is the cost of a single selection on s using the join condition. We have seen in Section 15.3 how to estimate the cost of a single selection algorithm (possibly using indices); that estimate gives us the value of c .

The cost formula indicates that, if indices are available on both relations r and s , it is generally most efficient to use the one with fewer tuples as the outer relation.

For example, consider an indexed nested-loop join of *student* \bowtie *takes*, with *student* as the outer relation. Suppose also that *takes* has a clustering B⁺-tree index on the join attribute *ID*, which contains 20 entries on average in each index node. Since *takes* has 10,000 tuples, the height of the tree is 4, and one more access is needed to find the actual data. Since n_{student} is 5000, the total cost is $100 + 5000 * 5 = 25,100$ disk accesses, each of which requires a seek and a block transfer. In contrast, as we saw before, 40,100 block transfers plus 200 seeks were needed for a block nested-loop join. Although the number of block transfers has been reduced, the seek cost has actually increased, increasing the total cost since a seek is considerably more expensive than a block transfer. However, if we had a selection on the *student* relation that reduces the number of rows significantly, indexed nested-loop join could be significantly faster than block nested-loop join.

15.5.4 Merge Join

The **merge-join** algorithm (also called the **sort-merge-join** algorithm) can be used to compute natural joins and equi-joins. Let $r(R)$ and $s(S)$ be the relations whose natural join is to be computed, and let $R \cap S$ denote their common attributes. Suppose that both relations are sorted on the attributes $R \cap S$. Then, their join can be computed by a process much like the merge stage in the merge-sort algorithm.

15.5.4.1 Merge-Join Algorithm

Figure 15.7 shows the merge-join algorithm. In the algorithm, *JoinAttrs* refers to the attributes in $R \cap S$, and $t_r \bowtie t_s$, where t_r and t_s are tuples that have the same values for *JoinAttrs*, denotes the concatenation of the attributes of the tuples, followed by projecting out repeated attributes. The merge-join algorithm associates one pointer with each relation. These pointers point initially to the first tuple of the respective relations. As the algorithm proceeds, the pointers move through the relation. A group of tuples of one relation with the same value on the join attributes is read into S_s . The algorithm in Figure 15.7 *requires* that every set of tuples S_s fit in main memory; we discuss extensions of the algorithm to avoid this requirement shortly. Then, the corresponding tuples (if any) of the other relation are read in and are processed as they are read.

Figure 15.8 shows two relations that are sorted on their join attribute *a1*. It is instructive to go through the steps of the merge-join algorithm on the relations shown in the figure.

The merge-join algorithm of Figure 15.7 requires that each set S_s of all tuples with the same value for the join attributes must fit in main memory. This requirement can usually be met, even if the relation s is large. If there are some join attribute values for

```

pr := address of first tuple of r;
ps := address of first tuple of s;
while (ps ≠ null and pr ≠ null) do
  begin
    ts := tuple to which ps points;
    Ss := {ts};
    set ps to point to next tuple of s;
    done := false;
    while (not done and ps ≠ null) do
      begin
        t's := tuple to which ps points;
        if (t's[JoinAttrs] = ts[JoinAttrs])
          then begin
            Ss := Ss ∪ {t's};
            set ps to point to next tuple of s;
          end
        else done := true;
      end
    end
    tr := tuple to which pr points;
    while (pr ≠ null and tr[JoinAttrs] < ts[JoinAttrs]) do
      begin
        set pr to point to next tuple of r;
        tr := tuple to which pr points;
      end
    while (pr ≠ null and tr[JoinAttrs] = ts[JoinAttrs]) do
      begin
        for each ts in Ss do
          begin
            add ts ⋈ tr to result;
          end
        set pr to point to next tuple of r;
        tr := tuple to which pr points;
      end
    end
  end
end.

```

Figure 15.7 Merge join.

which S_s is larger than available memory, a block nested-loop join can be performed for such sets S_s , matching them with corresponding blocks of tuples in r with the same values for the join attributes.

	<i>a1</i>	<i>a2</i>		<i>a1</i>	<i>a3</i>
$pr \rightarrow$	a	3	$ps \rightarrow$	a	A
	b	1		b	G
	d	8		c	L
	d	13		d	N
	f	7		m	B
	m	5			
	q	6			
	<i>r</i>			<i>s</i>	

Figure 15.8 Sorted relations for merge join.

If either of the input relations r and s is not sorted on the join attributes, they can be sorted first, and then the merge-join algorithm can be used. The merge-join algorithm can also be easily extended from natural joins to the more general case of equi-joins.

15.5.4.2 Cost Analysis

Once the relations are in sorted order, tuples with the same value on the join attributes are in consecutive order. Thereby, each tuple in the sorted order needs to be read only once, and, as a result, each block is also read only once. Since it makes only a single pass through both files (assuming all sets S_s fit in memory), the merge-join method is efficient; the number of block transfers is equal to the sum of the number of blocks in both files, $b_r + b_s$.

Assuming that b_b buffer blocks are allocated to each relation, the number of disk seeks required would be $\lceil b_r/b_b \rceil + \lceil b_s/b_b \rceil$ disk seeks. Since seeks are much more expensive than data transfer, it makes sense to allocate multiple buffer blocks to each relation, provided extra memory is available. For example, with $t_T = 0.1$ milliseconds per 4-kilobyte block, and $t_S = 4$ milliseconds, the buffer size is 400 blocks (or 1.6 megabytes), so the seek time would be 4 milliseconds for every 40 milliseconds of transfer time; in other words, seek time would be just 10 percent of the transfer time.

If either of the input relations r and s is not sorted on the join attributes, they must be sorted first; the cost of sorting must then be added to the above costs. If some sets S_s do not fit in memory, the cost would increase slightly.

Suppose the merge-join scheme is applied to our example of *student* \bowtie *takes*. The join attribute here is *ID*. Suppose that the relations are already sorted on the join attribute *ID*. In this case, the merge join takes a total of $400 + 100 = 500$ block transfers. If we assume that in the worst case only one buffer block is allocated to each input relation (that is, $b_b = 1$), a total of $400 + 100 = 500$ seeks would also be required; in reality b_b can be set much higher since we need to buffer blocks for only two relations, and the seek cost would be significantly less.

Suppose the relations are not sorted, and the memory size is the worst case, only three blocks. The cost is as follows:

1. Using the formulae that we developed in Section 15.4, we can see that sorting relation *takes* requires $\lceil \log_{3-1}(400/3) \rceil = 8$ merge passes. Sorting of relation *takes* then takes $400 * (2 \lceil \log_{3-1}(400/3) \rceil + 1)$, or 6800, block transfers, with 400 more transfers to write out the result. The number of seeks required is $2 * \lceil 400/3 \rceil + 400 * (2 * 8 - 1)$ or 6268 seeks for sorting, and 400 seeks for writing the output, for a total of 6668 seeks, since only one buffer block is available for each run.
2. Similarly, sorting relation *student* takes $\lceil \log_{3-1}(100/3) \rceil = 6$ merge passes and $100 * (2 \lceil \log_{3-1}(100/3) \rceil + 1)$, or 1300, block transfers, with 100 more transfers to write it out. The number of seeks required for sorting *student* is $2 * \lceil 100/3 \rceil + 100 * (2 * 6 - 1) = 1168$, and 100 seeks are required for writing the output, for a total of 1268 seeks.
3. Finally, merging the two relations takes $400 + 100 = 500$ block transfers and 500 seeks.

Thus, the total cost is 9100 block transfers plus 8932 seeks if the relations are not sorted, and the memory size is just 3 blocks.

With a memory size of 25 blocks, and the relations not sorted, the cost of sorting followed by merge join would be as follows:

1. Sorting the relation *takes* can be done with just one merge step and takes a total of just $400 * (2 \lceil \log_{24}(400/25) \rceil + 1) = 1200$ block transfers. Similarly, sorting *student* takes 300 block transfers. Writing the sorted output to disk requires $400 + 100 = 500$ block transfers, and the merge step requires 500 block transfers to read the data back. Adding up these costs gives a total cost of 2500 block transfers.
2. If we assume that only one buffer block is allocated for each run, the number of seeks required in this case is $2 * \lceil 400/25 \rceil + 400 + 400 = 832$ seeks for sorting *takes* and writing the sorted output to disk, and similarly $2 * \lceil 100/25 \rceil + 100 + 100 = 208$ for *student*, plus $400 + 100$ seeks for reading the sorted data in the merge-join step. Adding up these costs gives a total cost of 1640 seeks.

The number of seeks can be significantly reduced by setting aside more buffer blocks for each run. For example, if 5 buffer blocks are allocated for each run and for the output from merging the 4 runs of *student*, the cost is reduced to $2 * \lceil 100/25 \rceil + \lceil 100/5 \rceil + \lceil 100/5 \rceil = 48$ seeks, from 208 seeks. If the merge-join step sets aside 12 blocks each for buffering *takes* and *student*, the number of seeks for the merge-join step goes down to $\lceil 400/12 \rceil + \lceil 100/12 \rceil = 43$, from 500. The total number of seeks is then 251.

Thus, the total cost is 2500 block transfers plus 251 seeks if the relations are not sorted, and the memory size is 25 blocks.

15.5.4.3 Hybrid Merge Join

It is possible to perform a variation of the merge-join operation on unsorted tuples, if secondary indices exist on both join attributes. The algorithm scans the records through the indices, resulting in their being retrieved in sorted order. This variation presents a significant drawback, however, since records may be scattered throughout the file blocks. Hence, each tuple access could involve accessing a disk block, and that is costly.

To avoid this cost, we can use a hybrid merge-join technique that combines indices with merge join. Suppose that one of the relations is sorted; the other is unsorted, but has a secondary B⁺-tree index on the join attributes. The **hybrid merge-join algorithm** merges the sorted relation with the leaf entries of the secondary B⁺-tree index. The result file contains tuples from the sorted relation and addresses for tuples of the unsorted relation. The result file is then sorted on the addresses of tuples of the unsorted relation, allowing efficient retrieval of the corresponding tuples, in physical storage order, to complete the join. Extensions of the technique to handle two unsorted relations are left as an exercise for you.

15.5.5 Hash Join

Like the merge-join algorithm, the hash-join algorithm can be used to implement natural joins and equi-joins. In the hash-join algorithm, a hash function h is used to partition tuples of both relations. The basic idea is to partition the tuples of each of the relations into sets that have the same hash value on the join attributes.

We assume that:

- h is a hash function mapping *JoinAttrs* values to $\{0, 1, \dots, n_h\}$, where *JoinAttrs* denotes the common attributes of r and s used in the natural join.
- r_0, r_1, \dots, r_{n_h} denote partitions of r tuples, each initially empty. Each tuple $t_r \in r$ is put in partition r_i , where $i = h(t_r[\text{JoinAttrs}])$.
- s_0, s_1, \dots, s_{n_h} denote partitions of s tuples, each initially empty. Each tuple $t_s \in s$ is put in partition s_i , where $i = h(t_s[\text{JoinAttrs}])$.

The hash function h should have the “goodness” properties of randomness and uniformity that we discussed in Chapter 14. Figure 15.9 depicts the partitioning of the relations.

15.5.5.1 Basics

The idea behind the hash-join algorithm is this: Suppose that an r tuple and an s tuple satisfy the join condition; then, they have the same value for the join attributes. If that value is hashed to some value i , the r tuple has to be in r_i and the s tuple in s_i . Therefore,




Figure 15.9 Hash partitioning of relations.

r tuples in r_i need only be compared with s tuples in s_i ; they do not need to be compared with s tuples in any other partition.

For example, if d is a tuple in *student*, c a tuple in *takes*, and h a hash function on the *ID* attributes of the tuples, then d and c must be tested only if $h(c) = h(d)$. If $h(c) \neq h(d)$, then c and d must have different values for *ID*. However, if $h(c) = h(d)$, we must test c and d to see whether the values in their join attributes are the same, since it is possible that c and d have different *iids* that have the same hash value.

Figure 15.10 shows the details of the **hash-join** algorithm to compute the natural join of relations r and s . As in the merge-join algorithm, $t_r \bowtie t_s$ denotes the concatenation of the attributes of tuples t_r and t_s , followed by projecting out repeated attributes. After the partitioning of the relations, the rest of the hash-join code performs a separate indexed nested-loop join on each of the partition pairs i , for $i = 0, \dots, n_h$. To do so, it first **builds** a hash index on each s_i , and then **probes** (that is, looks up s_i) with tuples from r_i . The relation s is the **build input**, and r is the **probe input**.

The hash index on s_i is built in memory, so there is no need to access the disk to retrieve the tuples. The hash function used to build this hash index must be different from the hash function h used earlier, but it is still applied to only the join attributes. In the course of the indexed nested-loop join, the system uses this hash index to retrieve records that match records in the probe input.

The build and probe phases require only a single pass through both the build and probe inputs. It is straightforward to extend the hash-join algorithm to compute general equi-joins.

The value n_h must be chosen to be large enough such that, for each i , the tuples in the partition s_i of the build relation, along with the hash index on the partition, fit in memory. It is not necessary for the partitions of the probe relation to fit in memory. It is

```

/* Partition  $s$  */
for each tuple  $t_s$  in  $s$  do begin
     $i := h(t_s[JoinAttrs]);$ 
     $H_{s_i} := H_{s_i} \cup \{t_s\};$ 
end
/* Partition  $r$  */
for each tuple  $t_r$  in  $r$  do begin
     $i := h(t_r[JoinAttrs]);$ 
     $H_{r_i} := H_{r_i} \cup \{t_r\};$ 
end
/* Perform join on each partition */
for  $i := 0$  to  $n_h$  do begin
    read  $H_{s_i}$  and build an in-memory hash index on it;
    for each tuple  $t_r$  in  $H_{r_i}$  do begin
        probe the hash index on  $H_{s_i}$  to locate all tuples  $t_s$ 
        such that  $t_s[JoinAttrs] = t_r[JoinAttrs];$ 
        for each matching tuple  $t_s$  in  $H_{s_i}$  do begin
            add  $t_r \bowtie t_s$  to the result;
        end
    end
end

```

Figure 15.10 Hash join.

best to use the smaller input relation as the build relation. If the size of the build relation is b_s blocks, then, for each of the n_h partitions to be of size less than or equal to M , n_h must be at least $\lceil b_s/M \rceil$. More precisely stated, we have to account for the extra space occupied by the hash index on the partition as well, so n_h should be correspondingly larger. For simplicity, we sometimes ignore the space requirement of the hash index in our analysis.

15.5.5.2 Recursive Partitioning

If the value of n_h is greater than or equal to the number of blocks of memory, the relations cannot be partitioned in one pass, since there will not be enough buffer blocks. Instead, partitioning has to be done in repeated passes. In one pass, the input can be split into at most as many partitions as there are blocks available for use as output buffers. Each bucket generated by one pass is separately read in and partitioned again in the next pass, to create smaller partitions. The hash function used in a pass is different from the one used in the previous pass. The system repeats this splitting of the

input until each partition of the build input fits in memory. Such partitioning is called **recursive partitioning**.

A relation does not need recursive partitioning if $M > n_h + 1$, or equivalently $M > (b_s/M) + 1$, which simplifies (approximately) to $M > \sqrt{b_s}$. For example, consider a memory size of 12 megabytes, divided into 4-kilobyte blocks; it would contain a total of 3-kilobyte (3072) blocks. We can use a memory of this size to partition relations of size up to 3-kilobyte * 3-kilobyte blocks, which is 36 gigabytes. Similarly, a relation of size 1 gigabyte requires just over $\sqrt{256K}$ blocks, or 2 megabytes, to avoid recursive partitioning.

15.5.5.3 Handling of Overflows

Hash-table overflow occurs in partition i of the build relation s if the hash index on s_i is larger than main memory. Hash-table overflow can occur if there are many tuples in the build relation with the same values for the join attributes, or if the hash function does not have the properties of randomness and uniformity. In either case, some of the partitions will have more tuples than the average, whereas others will have fewer; partitioning is then said to be **skewed**.

We can handle a small amount of skew by increasing the number of partitions so that the expected size of each partition (including the hash index on the partition) is somewhat less than the size of memory. The number of partitions is therefore increased by a small value, called the **fudge factor**, that is usually about 20 percent of the number of hash partitions computed as described in Section 15.5.5.

Even if, by using a fudge factor, we are conservative on the sizes of the partitions, overflows can still occur. Hash-table overflows can be handled by either *overflow resolution* or *overflow avoidance*. **Overflow resolution** is performed during the build phase if a hash-index overflow is detected. Overflow resolution proceeds in this way: If s_i , for any i , is found to be too large, it is further partitioned into smaller partitions by using a different hash function. Similarly, r_i is also partitioned using the new hash function, and only tuples in the matching partitions need to be joined.

In contrast, **overflow avoidance** performs the partitioning carefully, so that overflows never occur during the build phase. In overflow avoidance, the build relation s is initially partitioned into many small partitions, and then some partitions are combined in such a way that each combined partition fits in memory. The probe relation r is partitioned in the same way as the combined partitions on s , but the sizes of r_i do not matter.

If a large number of tuples in s have the same value for the join attributes, the resolution and avoidance techniques may fail on some partitions. In that case, instead of creating an in-memory hash index and using a nested-loop join to join the partitions, we can use other join techniques, such as block nested-loop join, on those partitions.

15.5.5.4 Cost of Hash Join

We now consider the cost of a hash join. Our analysis assumes that there is no hash-table overflow. First, consider the case where recursive partitioning is not required.

- The partitioning of the two relations r and s calls for a complete reading of both relations and a subsequent writing back of them. This operation requires $2(b_r + b_s)$ block transfers, where b_r and b_s denote the number of blocks containing records of relations r and s , respectively. The build and probe phases read each of the partitions once, calling for further $b_r + b_s$ block transfers. The number of blocks occupied by partitions could be slightly more than $b_r + b_s$, as a result of partially filled blocks. Accessing such partially filled blocks can add an overhead of at most $2n_h$ for each of the relations, since each of the n_h partitions could have a partially filled block that has to be written and read back. Thus, a hash join is estimated to require:

$$3(b_r + b_s) + 4n_h$$

block transfers. The overhead $4n_h$ is usually quite small compared to $b_r + b_s$ and can be ignored.

- Assuming b_b blocks are allocated for the input buffer and each output buffer, partitioning requires a total of $2(\lceil b_r/b_b \rceil + \lceil b_s/b_b \rceil)$ seeks. The build and probe phases require only one seek for each of the n_h partitions of each relation, since each partition can be read sequentially. The hash join thus requires $2(\lceil b_r/b_b \rceil + \lceil b_s/b_b \rceil) + 2n_h$ seeks.

Now consider the case where recursive partitioning is required. Again we assume that b_b blocks are allocated for buffering each partition. Each pass then reduces the size of each of the partitions by an expected factor of $\lfloor M/b_b \rfloor - 1$; and passes are repeated until each partition is of size at most M blocks. The expected number of passes required for partitioning s is therefore $\lceil \log_{\lfloor M/b_b \rfloor - 1}(b_s/M) \rceil$.

- Since, in each pass, every block of s is read in and written out, the total number of block transfers for partitioning of s is $2b_s \lceil \log_{\lfloor M/b_b \rfloor - 1}(b_s/M) \rceil$. The number of passes for partitioning of r is the same as the number of passes for partitioning of s , therefore the join is estimated to require

$$2(b_r + b_s) \lceil \log_{\lfloor M/b_b \rfloor - 1}(b_s/M) \rceil + b_r + b_s$$

block transfers.

- Ignoring the relatively small number of seeks during the build and probe phases, hash join with recursive partitioning requires

$$2(\lceil b_r/b_b \rceil + \lceil b_s/b_b \rceil) \lceil \log_{\lfloor M/b_b \rfloor - 1}(b_s/M) \rceil$$

disk seeks.

Consider, for example, the natural join *takes* \bowtie *student*. With a memory size of 20 blocks, the *student* relation can be partitioned into five partitions, each of size 20 blocks, which size will fit into memory. Only one pass is required for the partitioning. The

relation *takes* is similarly partitioned into five partitions, each of size 80. Ignoring the cost of writing partially filled blocks, the cost is $3(100 + 400) = 1500$ block transfers. There is enough memory to allocate the buffers for the input and each of the five outputs during partitioning (i.e., $b_b = 3$) leading to $2(\lceil 100/3 \rceil + \lceil 400/3 \rceil) = 336$ seeks.

The hash join can be improved if the main memory size is large. When the entire build input can be kept in main memory, n_h can be set to 0; then, the hash-join algorithm executes quickly, without partitioning the relations into temporary files, regardless of the probe input's size. The cost estimate goes down to $b_r + b_s$ block transfers and two seeks.

Indexed nested loops join can have a much lower cost than hash join in case the outer relation is small, and the index lookups fetch only a few tuples from the inner (indexed) relation. However, in case a secondary index is used, and the number of tuples in the outer relation is large, indexed nested loops join can have a very high cost, as compared to hash join. If the number of tuples in the outer relation is known at query optimization time, the best join algorithm can be chosen at that time. However, in some cases, for example, when there is a selection condition on the outer input, the optimizer makes a decision based on an estimate that may potentially be imprecise. The number of tuples in the outer relation may be found only at runtime, for example, after executing selection. Some systems allow a dynamic choice between the two algorithms at run time, after finding the number of tuples in the outer input.

15.5.5.5 Hybrid Hash Join

The **hybrid hash-join** algorithm performs another optimization; it is useful when memory sizes are relatively large but not all of the build relation fits in memory. The partitioning phase of the hash-join algorithm needs a minimum of one block of memory as a buffer for each partition that is created, and one block of memory as an input buffer. To reduce the impact of seeks, a larger number of blocks would be used as a buffer; let b_b denote the number of blocks used as a buffer for the input and for each partition. Hence, a total of $(n_h + 1) * b_b$ blocks of memory are needed for partitioning the two relations. If memory is larger than $(n_h + 1) * b_b$, we can use the rest of memory ($M - (n_h + 1) * b_b$ blocks) to buffer the first partition of the build input (i.e., s_0) so that it will not need to be written out and read back in. Further, the hash function is designed in such a way that the hash index on s_0 fits in $M - (n_h + 1) * b_b$ blocks, in order that, at the end of partitioning of s , s_0 is completely in memory and a hash index can be built on s_0 .

When the system partitions r , it again does not write tuples in r_0 to disk; instead, as it generates them, the system uses them to probe the memory-resident hash index on s_0 , and to generate output tuples of the join. After they are used for probing, the tuples can be discarded, so the partition r_0 does not occupy any memory space. Thus, a write and a read access have been saved for each block of both r_0 and s_0 . The system writes out tuples in the other partitions as usual and joins them later. The savings of hybrid hash join can be significant if the build input is only slightly bigger than memory.

If the size of the build relation is b_s , n_h is approximately equal to b_s/M . Thus, hybrid hash join is most useful if $M \gg (b_s/M) * b_b$, or $M \gg \sqrt{b_s * b_b}$, where the notation \gg denotes *much larger than*. For example, suppose the block size is 4 kilobytes, the build relation size is 5 gigabytes, and b_b is 20. Then, the hybrid hash-join algorithm is useful if the size of memory is significantly more than 20 megabytes; memory sizes of gigabytes or more are common on computers today. If we devote 1 gigabyte for the join algorithm, s_0 would be nearly 1 gigabyte, and hybrid hash join would be nearly 20 percent cheaper than hash join.

15.5.6 Complex Joins

Nested-loop and block nested-loop joins can be used regardless of the join conditions. The other join techniques are more efficient than the nested-loop join and its variants, but they can handle only simple join conditions, such as natural joins or equi-joins. We can implement joins with complex join conditions, such as conjunctions and disjunctions, by using the efficient join techniques, if we apply the techniques developed in Section 15.3.3 for handling complex selections.

Consider the following join with a conjunctive condition:

$$r \bowtie_{\theta_1 \wedge \theta_2 \wedge \dots \wedge \theta_n} s$$

One or more of the join techniques described earlier may be applicable for joins on the individual conditions $r \bowtie_{\theta_1} s$, $r \bowtie_{\theta_2} s$, $r \bowtie_{\theta_3} s$, and so on. We can compute the overall join by first computing the result of one of these simpler joins $r \bowtie_{\theta_i} s$; each pair of tuples in the intermediate result consists of one tuple from r and one from s . The result of the complete join consists of those tuples in the intermediate result that satisfy the remaining conditions:

$$\theta_1 \wedge \dots \wedge \theta_{i-1} \wedge \theta_{i+1} \wedge \dots \wedge \theta_n$$

These conditions can be tested as tuples in $r \bowtie_{\theta_i} s$ are being generated.

A join whose condition is disjunctive can be computed in this way. Consider:

$$r \bowtie_{\theta_1 \vee \theta_2 \vee \dots \vee \theta_n} s$$

The join can be computed as the union of the records in individual joins $r \bowtie_{\theta_i} s$:

$$(r \bowtie_{\theta_1} s) \cup (r \bowtie_{\theta_2} s) \cup \dots \cup (r \bowtie_{\theta_n} s)$$

Section 15.6 describes algorithms for computing the union of relations.

15.5.7 Joins over Spatial Data

The join algorithms we have presented make no specific assumptions about the type of data being joined, but they do assume the use of standard comparison operations such as equality, less than, or greater than, where the values are linearly ordered.

Selection and join conditions on spatial data involve comparison operators that check if one region contains or overlaps another, or whether a region contains a particular point; and the regions may be multi-dimensional. Comparisons may pertain also to the distance between points, for example, finding a set of points closest to a given point in a two-dimensional space.

Merge-join cannot be used with such comparison operations, since there is no simple sort order over spatial data in two or more dimensions. Partitioning of data based on hashing is also not applicable, since there is no way to ensure that tuples that satisfy an overlap or containment predicate are hashed to the same value. Nested loops join can always be used regardless of the complexity of the conditions, but can be very inefficient on large datasets.

Indexed nested-loops join can however be used, if appropriate spatial indices are available. In Section 14.10, we saw several types of indices for spatial data, including R-trees, k-d trees, k-d-B trees, and quadtrees. Additional details on those indices appear in Section 24.4. These index structures enable efficient retrieval of spatial data based on predicates such as contains, contained in, or overlaps, and can also be effectively used to find nearest neighbors.

Most major database systems today incorporate support for indexing spatial data, and make use of them when processing queries using spatial comparison conditions.

15.6 Other Operations

Other relational operations and extended relational operations—such as duplicate elimination, projection, set operations, outer join, and aggregation—can be implemented as outlined in Section 15.6.1 through Section 15.6.5.

15.6.1 Duplicate Elimination

We can implement duplicate elimination easily by sorting. Identical tuples will appear adjacent to each other as a result of sorting, and all but one copy can be removed. With external sort-merge, duplicates found while a run is being created can be removed before the run is written to disk, thereby reducing the number of block transfers. The remaining duplicates can be eliminated during merging, and the final sorted run has no duplicates. The worst-case cost estimate for duplicate elimination is the same as the worst-case cost estimate for sorting of the relation.

We can also implement duplicate elimination by hashing, as in the hash-join algorithm. First, the relation is partitioned on the basis of a hash function on the whole tuple. Then, each partition is read in, and an in-memory hash index is constructed.

While constructing the hash index, a tuple is inserted only if it is not already present. Otherwise, the tuple is discarded. After all tuples in the partition have been processed, the tuples in the hash index are written to the result. The cost estimate is the same as that for the cost of processing (partitioning and reading each partition) of the build relation in a hash join.

Because of the relatively high cost of duplicate elimination, SQL requires an explicit request by the user to remove duplicates; otherwise, the duplicates are retained.

15.6.2 Projection

We can implement projection easily by performing projection on each tuple, which gives a relation that could have duplicate records, and then removing duplicate records. Duplicates can be eliminated by the methods described in Section 15.6.1. If the attributes in the projection list include a key of the relation, no duplicates will exist; hence, duplicate elimination is not required. Generalized projection can be implemented in the same way as projection.

15.6.3 Set Operations

We can implement the *union*, *intersection*, and *set-difference* operations by first sorting both relations, and then scanning once through each of the sorted relations to produce the result. In $r \cup s$, when a concurrent scan of both relations reveals the same tuple in both files, only one of the tuples is retained. The result of $r \cap s$ will contain only those tuples that appear in both relations. We implement *set difference*, $r - s$, similarly, by retaining tuples in r only if they are absent in s .

For all these operations, only one scan of the two sorted input relations is required, so the cost is $b_r + b_s$ block transfers if the relations are sorted in the same order. Assuming a worst case of one block buffer for each relation, a total of $b_r + b_s$ disk seeks would be required in addition to $b_r + b_s$ block transfers. The number of seeks can be reduced by allocating extra buffer blocks.

If the relations are not sorted initially, the cost of sorting has to be included. Any sort order can be used in the evaluation of set operations, provided that both inputs have that same sort order.

Hashing provides another way to implement these set operations. The first step in each case is to partition the two relations by the same hash function and thereby create the partitions r_0, r_1, \dots, r_{n_h} and s_0, s_1, \dots, s_{n_h} . Depending on the operation, the system then takes these steps on each partition $i = 0, 1, \dots, n_h$:

- $r \cup s$
 1. Build an in-memory hash index on r_i .
 2. Add the tuples in s_i to the hash index only if they are not already present.
 3. Add the tuples in the hash index to the result.

Note 15.1 Answering Keyword Queries

Keyword search on documents is widely used in the context of web search. In its simplest form, a keyword query provides a set of words K_1, K_2, \dots, K_n , and the goal is to find documents d_i from a collection of documents D such that d_i contains all the keywords in the query. Real-life keyword search is more complicated, since it requires ranking of documents based on various metrics such TF-IDF and PageRank, as we saw earlier in Section 8.3.

Documents that contain a specified keyword can be located efficiently by using an index (often referred to as an **inverted index**) that maps each keyword K_i to a list S_i of identifiers of the documents that contain K_i . The list is kept sorted. For example, if documents d_1 , d_9 and d_{21} contain the term “Silberschatz”, the inverted list for the keyword Silberschatz would be “ $d_1; d_9; d_{21}$ ”. Compression techniques are used to reduce the size of the inverted lists. A B^+ -tree index can be used to map each keyword K_i to its associated inverted list S_i .

To answer a query with keyword K_1, K_2, \dots, K_n , we retrieve the inverted list S_i for each keyword K_i , and then compute the intersection $S_1 \cap S_2 \cap \dots \cap S_n$ to find documents that appear in all the lists. Since the lists are sorted, the intersection can be efficiently implemented by merging the lists using concurrent scans of all the lists. Many information-retrieval systems return documents that contain several, even if not all, of the keywords; the merge step can be easily modified to output documents that contain at least k of the n keywords.

To support ranking of keyword-query results, extra information can be stored in each inverted list, including the inverse document frequency of the term, and for each document the PageRank, the term frequency of the term, as well as the positions within the document where the term occurs. This information can be used to compute scores that are then used to rank the documents. For example, documents where the keywords occur close to each other may receive a higher score for keyword proximity than those where they occur farther from each other. The keyword proximity score may be combined with the TF-IDF score, and PageRank to compute an overall score. Documents are then ranked on this score. Since most web searches retrieve only the top few answers, search engines incorporate a number of optimizations that help to find the top few answers efficiently, without computing the full list and then finding the ranking. References providing further details may be found in the Further Reading section at the end of the chapter.

- $r \cap s$
 1. Build an in-memory hash index on r_i .
 2. For each tuple in s_i , probe the hash index and output the tuple to the result only if it is already present in the hash index.

- $r - s$
 1. Build an in-memory hash index on r_i .
 2. For each tuple in s_i , probe the hash index, and, if the tuple is present in the hash index, delete it from the hash index.
 3. Add the tuples remaining in the hash index to the result.

15.6.4 Outer Join

Recall the *outer-join operations* described in Section 4.1.3. For example, the natural left outer join $takes \bowtie_{\text{student}}$ contains the join of *takes* and *student*, and, in addition, for each *takes* tuple t that has no matching tuple in *student* (i.e., where *ID* is not in *student*), the following tuple t_1 is added to the result. For all attributes in the schema of *takes*, tuple t_1 has the same values as tuple t . The remaining attributes (from the schema of *student*) of tuple t_1 contain the value null.

We can implement the outer-join operations by using one of two strategies:

1. Compute the corresponding join, and then add further tuples to the join result to get the outer-join result. Consider the left outer-join operation and two relations: $r(R)$ and $s(S)$. To evaluate $r \bowtie_{\theta} s$, we first compute $r \bowtie_{\theta} s$ and save that result as temporary relation q_1 . Next, we compute $r - \Pi_R(q_1)$ to obtain those tuples in r that do not participate in the theta join. We can use any of the algorithms for computing the joins, projection, and set difference described earlier to compute the outer joins. We pad each of these tuples with null values for attributes from s , and add it to q_1 to get the result of the outer join.
 The right outer-join operation $r \bowtie_{\theta} s$ is equivalent to $s \bowtie_{\theta} r$ and can therefore be implemented in a symmetric fashion to the left outer join. We can implement the full outer-join operation $r \bowtie_{\theta} s$ by computing the join $r \bowtie s$ and then adding the extra tuples of both the left and right outer-join operations, as before.
2. Modify the join algorithms. It is easy to extend the nested-loop join algorithms to compute the left outer join: Tuples in the outer relation that do not match any tuple in the inner relation are written to the output after being padded with null values. However, it is hard to extend the nested-loop join to compute the full outer join.

Natural outer joins and outer joins with an equi-join condition can be computed by extensions of the merge-join and hash-join algorithms. Merge join can be extended to compute the full outer join as follows: When the merge of the two relations is being done, tuples in either relation that do not match any tuple in the other relation can be padded with nulls and written to the output. Similarly, we can extend merge join to compute the left and right outer joins by writing out nonmatching tuples (padded with nulls) from only one of the relations. Since the relations are sorted, it is easy to detect whether or not a tuple matches any tuples

from the other relation. For example, when a merge join of *takes* and *student* is done, the tuples are read in sorted order of *ID*, and it is easy to check, for each tuple, whether there is a matching tuple in the other.

The cost estimates for implementing outer joins using the merge-join algorithm are the same as are those for the corresponding join. The only difference lies in the size of the result, and therefore in the block transfers for writing it out, which we did not count in our earlier cost estimates.

The extension of the hash-join algorithm to compute outer joins is left for you to do as an exercise (Exercise 15.21).

15.6.5 Aggregation

Recall the aggregation function (operator), discussed in Section 3.7. For example, the function

```
select dept_name, avg (salary)
from instructor
group by dept_name;
```

computes the average salary in each university department.

The aggregation operation can be implemented in the same way as duplicate elimination. We use either sorting or hashing, just as we did for duplicate elimination, but based on the grouping attributes (*dept_name* in the preceding example). However, instead of eliminating tuples with the same value for the grouping attribute, we gather them into groups and apply the aggregation operations on each group to get the result.

The cost estimate for implementing the aggregation operation is the same as the cost of duplicate elimination for aggregate functions such as **min**, **max**, **sum**, **count**, and **avg**.

Instead of gathering all the tuples in a group and then applying the aggregation operations, we can implement the aggregation operations **sum**, **min**, **max**, **count**, and **avg** on the fly as the groups are being constructed. For the case of **sum**, **min**, and **max**, when two tuples in the same group are found, the system replaces them with a single tuple containing the **sum**, **min**, or **max**, respectively, of the columns being aggregated. For the **count** operation, it maintains a running count for each group for which a tuple has been found. Finally, we implement the **avg** operation by computing the sum and the count values on the fly, and finally dividing the sum by the count to get the average.

If all tuples of the result fit in memory, the sort-based and the hash-based implementations do not need to write any tuples to disk. As the tuples are read in, they can be inserted in a sorted tree structure or in a hash index. When we use on-the-fly aggregation techniques, only one tuple needs to be stored for each of the groups. Hence, the sorted tree structure or hash index fits in memory, and the aggregation can be processed with just b_r block transfers (and 1 seek) instead of the $3b_r$ transfers (and a worst case of up to $2b_r$ seeks) that would be required otherwise.

15.7 Evaluation of Expressions

So far, we have studied how individual relational operations are carried out. Now we consider how to evaluate an expression containing multiple operations. The obvious way to evaluate an expression is simply to evaluate one operation at a time, in an appropriate order. The result of each evaluation is **materialized** in a temporary relation for subsequent use. A disadvantage to this approach is the need to construct the temporary relations, which (unless they are small) must be written to disk. An alternative approach is to evaluate several operations simultaneously in a **pipeline**, with the results of one operation passed on to the next, without the need to store a temporary relation.

In Section 15.7.1 and Section 15.7.2, we consider both the *materialization* approach and the *pipelining* approach. We shall see that the costs of these approaches can differ substantially, but also that there are cases where only the materialization approach is feasible.

15.7.1 Materialization

It is easiest to understand intuitively how to evaluate an expression by looking at a pictorial representation of the expression in an **operator tree**. Consider the expression:

$$\Pi_{name}(\sigma_{building = \text{"Watson"}}(department) \bowtie instructor)$$

in Figure 15.11.

If we apply the materialization approach, we start from the lowest-level operations in the expression (at the bottom of the tree). In our example, there is only one such operation: the selection operation on *department*. The inputs to the lowest-level operations are relations in the database. We execute these operations using the algorithms that we studied earlier, and we store the results in temporary relations. We can use these temporary relations to execute the operations at the next level up in the tree, where the inputs now are either temporary relations or relations stored in the database. In our




Figure 15.11 Pictorial representation of an expression.

example, the inputs to the join are the *instructor* relation and the temporary relation created by the selection on *department*. The join can now be evaluated, creating another temporary relation.

By repeating the process, we will eventually evaluate the operation at the root of the tree, giving the final result of the expression. In our example, we get the final result by executing the projection operation at the root of the tree, using as input the temporary relation created by the join.

Evaluation as just described is called **materialized evaluation**, since the results of each intermediate operation are created (materialized) and then are used for evaluation of the next-level operations.

The cost of a materialized evaluation is not simply the sum of the costs of the operations involved. When we computed the cost estimates of algorithms, we ignored the cost of writing the result of the operation to disk. To compute the cost of evaluating an expression as done here, we have to add the costs of all the operations, as well as the cost of writing the intermediate results to disk. We assume that the records of the result accumulate in a buffer, and, when the buffer is full, they are written to disk. The number of blocks written out, b_r , can be estimated as n_r/f_r , where n_r is the estimated number of tuples in the result relation r and f_r is the *blocking factor* of the result relation, that is, the number of records of r that will fit in a block. In addition to the transfer time, some disk seeks may be required, since the disk head may have moved between successive writes. The number of seeks can be estimated as $\lceil b_r/b_b \rceil$ where b_b is the size of the output buffer (measured in blocks).

Double buffering (using two buffers, with one continuing execution of the algorithm while the other is being written out) allows the algorithm to execute more quickly by performing CPU activity in parallel with I/O activity. The number of seeks can be reduced by allocating extra blocks to the output buffer and writing out multiple blocks at once.

15.7.2 Pipelining

We can improve query-evaluation efficiency by reducing the number of temporary files that are produced. We achieve this reduction by combining several relational operations into a *pipeline* of operations, in which the results of one operation are passed along to the next operation in the pipeline. Evaluation as just described is called **pipelined evaluation**.

For example, consider the expression $(\Pi_{a_1, a_2}(r \bowtie s))$. If materialization were applied, evaluation would involve creating a temporary relation to hold the result of the join and then reading back in the result to perform the projection. These operations can be combined: When the join operation generates a tuple of its result, it passes that tuple immediately to the project operation for processing. By combining the join and the projection, we avoid creating the intermediate result and instead create the final result directly.

Creating a pipeline of operations can provide two benefits:

1. It eliminates the cost of reading and writing temporary relations, reducing the cost of query evaluation. Note that the cost formulae that we saw earlier for each operation included the cost of reading the result from disk. If the input to an operator o_i is pipelined from a preceding operator o_j , the cost of o_i should not include the cost of reading the input from disk; the cost formulae that we saw earlier can be modified accordingly.
2. It can start generating query results quickly, if the root operator of a query-evaluation plan is combined in a pipeline with its inputs. This can be quite useful if the results are displayed to a user as they are generated, since otherwise there may be a long delay before the user sees any query results.

15.7.2.1 Implementation of Pipelining

We can implement a pipeline by constructing a single, complex operation that combines the operations that constitute the pipeline. Although this approach may be feasible for some frequently occurring situations, it is desirable in general to reuse the code for individual operations in the construction of a pipeline.

In the example of Figure 15.11, all three operations can be placed in a pipeline, which passes the results of the selection to the join as they are generated. In turn, it passes the results of the join to the projection as they are generated. The memory requirements are low, since results of an operation are not stored for long. However, as a result of pipelining, the inputs to the operations are not available all at once for processing.

Pipelines can be executed in either of two ways:

1. In a **demand-driven pipeline**, the system makes repeated requests for tuples from the operation at the top of the pipeline. Each time that an operation receives a request for tuples, it computes the next tuple (or tuples) to be returned and then returns that tuple. If the inputs of the operation are not pipelined, the next tuple(s) to be returned can be computed from the input relations, while the system keeps track of what has been returned so far. If it has some pipelined inputs, the operation also makes requests for tuples from its pipelined inputs. Using the tuples received from its pipelined inputs, the operation computes tuples for its output and passes them up to its parent.
2. In a **producer-driven pipeline**, operations do not wait for requests to produce tuples, but instead generate the tuples **eagerly**. Each operation in a producer-driven pipeline is modeled as a separate process or thread within the system that takes a stream of tuples from its pipelined inputs and generates a stream of tuples for its output.

We describe next how demand-driven and producer-driven pipelines can be implemented.

Each operation in a demand-driven pipeline can be implemented as an **iterator** that provides the following functions: *open()*, *next()*, and *close()*. After a call to *open()*, each call to *next()* returns the next output tuple of the operation. The implementation of the operation in turn calls *open()* and *next()* on its inputs, to get its input tuples when required. The function *close()* tells an iterator that no more tuples are required. The iterator maintains the **state** of its execution in between calls so that successive *next()* requests receive successive result tuples.

For example, for an iterator implementing the select operation using linear search, the *open()* operation starts a file scan, and the iterator's state records the point to which the file has been scanned. When the *next()* function is called, the file scan continues from after the previous point; when the next tuple satisfying the selection is found by scanning the file, the tuple is returned after storing the point where it was found in the iterator state. A merge-join iterator's *open()* operation would open its inputs, and if they are not already sorted, it would also sort the inputs. On calls to *next()*, it would return the next pair of matching tuples. The state information would consist of up to where each input had been scanned. Details of the implementation of iterators are left for you to complete in Practice Exercise 15.7.

Producer-driven pipelines, on the other hand, are implemented in a different manner. For each pair of adjacent operations in a producer-driven pipeline, the system creates a buffer to hold tuples being passed from one operation to the next. The processes or threads corresponding to different operations execute concurrently. Each operation at the bottom of a pipeline continually generates output tuples, and puts them in its output buffer, until the buffer is full. An operation at any other level of a pipeline generates output tuples when it gets input tuples from lower down in the pipeline until its output buffer is full. Once the operation uses a tuple from a pipelined input, it removes the tuple from its input buffer. In either case, once the output buffer is full, the operation waits until its parent operation removes tuples from the buffer so that the buffer has space for more tuples. At this point, the operation generates more tuples until the buffer is full again. The operation repeats this process until all the output tuples have been generated.

It is necessary for the system to switch between operations only when an output buffer is full or when an input buffer is empty and more input tuples are needed to generate any more output tuples. In a parallel-processing system, operations in a pipeline may be run concurrently on distinct processors (see Section 22.5.1).

Using producer-driven pipelining can be thought of as **pushing** data up an operation tree from below, whereas using demand-driven pipelining can be thought of as **pulling** data up an operation tree from the top. Whereas tuples are generated *eagerly* in producer-driven pipelining, they are generated *lazily*, on demand, in demand-driven pipelining. Demand-driven pipelining is used more commonly than producer-driven pipelining because it is easier to implement. However, producer-driven pipelining is very useful in parallel processing systems. Producer-driven pipelining has also been

found to be more efficient than demand-driven pipelining on modern CPUs since it reduces the number of function call invocations as compared to demand-driven pipelining. Producer-driven pipelining is increasingly used in systems that generate machine code for high performance query evaluation.

15.7.2.2 Evaluation Algorithms for Pipelining

Query plans can be annotated to mark edges that are pipelined; such edges are called **pipelined edges**. In contrast, non-pipelined edges are referred to as **blocking edges** or **materialized edges**. The two operators connected by a pipelined edge must be executed concurrently, since one consumes tuples as the other generates them. Since a plan can have multiple pipelined edges, the set of all operators that are connected by pipelined edges must be executed concurrently. A query plan can be divided into subtrees such that each subtree has only pipelined edges, and the edges between the subtrees are non-pipelined. Each such subtree is called a **pipeline stage**. The query processor executes the plan one pipeline stage at a time, and concurrently executes all the operators in a single pipeline stage.

Some operations, such as sorting, are inherently **blocking operations**, that is, they may not be able to output any results until all tuples from their inputs have been examined.⁷ But interestingly, blocking operators can consume tuples as they are generated, and can output tuples to their consumers as they are generated; such operations actually execute in two or more stages, and blocking actually happens between two stages of the operation.

For example, the external sort-merge operation actually has two steps: (i) run-generation, followed by (ii) merging. The run-generation step can accept tuples as they are generated by the input to the sort, and can thus be pipelined with the sort input. The merge step, on the other hand, can send tuples to its consumer as they are generated, and can thus be pipelined with the consumer of the sort operation. But the merge step can start only after the run-generation step has finished. We can thus model the sort-merge operator as two sub-operators connected to each other by a non-pipelined edge, but each of the sub-operators can be connected by pipelined edges to their input and output respectively.

Other operations, such as join, are not inherently blocking, but specific evaluation algorithms may be blocking. For example, the indexed nested loops join algorithm can output result tuples as it gets tuples for the outer relation. It is therefore pipelined on its outer (left-hand side) relation; however, it is blocking on its indexed (right-hand side) input, since the index must be fully constructed before the indexed nested-loop join algorithm can execute.

The hash-join algorithm is a blocking operation on both inputs, since it requires both its inputs to be fully retrieved and partitioned before it outputs any tuples. How-

⁷Blocking operations such as sorting may be able to output tuples early if the input is known to satisfy some special properties such as being sorted, or partially sorted, already. However, in the absence of such information, blocking operations cannot output tuples early.




Figure 15.12 Query plan with pipelining.

ever, hash-join partitions each of its inputs, and then performs multiple build-probe steps, once per partition. Thus, the hash-join algorithm has 3 steps: (i) partitioning of the first input, (ii) partitioning of the second input, and (iii) the build-probe step. The partitioning step for each input can accept tuples as they are generated by the input, and can thus be pipelined with its input. The build-probe step can output tuples to its consumer as the tuples are generated, and can thus be pipelined with its consumer. But the two partitioning steps are connected to the build-probe step by non-pipelined edges, since build-probe can start only after partitioning has been completed on both inputs.

Hybrid hash join can be viewed as partially pipelined on the probe relation, since it can output tuples from the first partition as tuples are received for the probe relation. However, tuples that are not in the first partition will be output only after the entire pipelined input relation is received. Hybrid hash join thus provides fully pipelined evaluation on its probe input if the build input fits entirely in memory, or nearly pipelined evaluation if most of the build input fits in memory.

Figure 15.12a shows a query that joins two relations r and s , and then performs an aggregation on the result; details of the join predicate, group by attributes and aggregation functions are omitted for simplicity. Figure 15.12b shows a pipelined plan for the query using hash join and in-memory hash aggregation. Pipelined edges are shown using a normal line, while blocking edges are shown using a bold line. Pipeline stages are enclosed in dashed boxes. Note that hash join has been split into three suboperators. Two of suboperators, shown abbreviated to *Part.*, partition r and s respectively. The third, abbreviated to *HJ-BP*, performs the build and probe phase of the hash join. The *HA-IM* operator is the in-memory hash aggregation operator. The edges from the partition operators to the *HJ-BP* operator are blocking edges, since the *HJ-BP* operator can start execution only after the partition operators have completed execution. The edges from the relations (assumed to be scanned using a relation scan operator) to the partition operators are pipelined, as is the edge from the *HJ-BP* operator to the *HA-IM* operator. The resultant pipeline stages are shown enclosed in dashed boxes.

In general, for each materialized edge we need to add the cost of writing the data to disk, and the cost of the consumer operator should include the cost of reading the data from disk. However, when a materialized edge is between suboperators of a single

```

doner := false;
dones := false;
r := ∅;
s := ∅;
result := ∅;
while not doner or not dones do
  begin
    if queue is empty, then wait until queue is not empty;
    t := top entry in queue;
    if t = Endr then doner := true
    else if t = Ends then dones := true
    else if t is from input r
      then
        begin
          r := r ∪ {t};
          result := result ∪ ({t} ⋈ s);
        end
      else /* t is from input s */
        begin
          s := s ∪ {t};
          result := result ∪ (r ⋈ {t});
        end
      end
    end
  end

```

Figure 15.13 Double-pipelined join algorithm.

operator, for example between run generation and merge, the materialization cost has already been accounted for in the operators cost, and should not be added again.

In some applications, a join algorithm that is pipelined on both its inputs and its output is desirable. If both inputs are sorted on the join attribute, and the join condition is an equi-join, merge join can be used, with both its inputs and its output pipelined.

However, in the more common case that the two inputs that we desire to pipeline into the join are not already sorted, another alternative is the **double-pipelined join** technique, shown in Figure 15.13. The algorithm assumes that the input tuples for both input relations, *r* and *s*, are pipelined. Tuples made available for both relations are queued for processing in a single queue. Special queue entries, called *End_r* and *End_s*, which serve as end-of-file markers, are inserted in the queue after all tuples from *r* and *s* (respectively) have been generated. For efficient evaluation, appropriate indices should be built on the relations *r* and *s*. As tuples are added to *r* and *s*, the indices must be kept

up to date. When hash indices are used on r and s , the resultant algorithm is called the **double-pipelined hash-join** technique.

The double-pipelined join algorithm in Figure 15.13 assumes that both inputs fit in memory. In case the two inputs are larger than memory, it is still possible to use the double-pipelined join technique as usual until available memory is full. When available memory becomes full, r and s tuples that have arrived up to that point can be treated as being in partition r_0 and s_0 , respectively. Tuples for r and s that arrive subsequently are assigned to partitions r_1 and s_1 , respectively, which are written to disk, and are not added to the in-memory index. However, tuples assigned to r_1 and s_1 are used to probe s_0 and r_0 , respectively, before they are written to disk. Thus, the join of r_1 with s_0 , and s_1 with r_0 , is also carried out in a pipelined fashion. After r and s have been fully processed, the join of r_1 tuples with s_1 tuples must be carried out to complete the join; any of the join techniques we have seen earlier can be used to join r_1 with s_1 .

15.7.3 Pipelines for Continuous-Stream Data

Pipelining is also applicable in situations where data are entered into the database in a continuous manner, as is the case, for example, for inputs from sensors that are continuously monitoring environmental data. Such data are called *data streams*, as we saw earlier in Section 10.5. Queries may be written over stream data in order to respond to data as they arrive. Such queries are called *continuous queries*.

The operations in a continuous query should be implemented using pipelined algorithms, so that results from the pipeline can be output without blocking. Producer-driven pipelines (which we discussed earlier in Section 15.7.2.1) are the best suited for continuous query evaluation.

Many such queries perform aggregation with windowing; tumbling windows which divide time into fixed size intervals, such as 1 minute, or 1 hour, are commonly used. Grouping and aggregation is performed separately on each window, as tuples are received; assuming memory size is large enough, an in-memory hash index is used to perform aggregation.

The result of aggregation on a window can be output once the system knows that no further tuples in that window will be received in future. If tuples are guaranteed to arrive sorted by timestamp, the arrival of a tuple of a following window indicates no more tuples will be received for an earlier window. If tuples may arrive out of order, streams must carry punctuations that indicate that all future tuples will have a timestamp greater than some specified value. The arrival of a punctuation allows the output of aggregates of windows whose end-timestamp is less than or equal to the timestamp specified by the punctuation.

15.8 Query Processing in Memory

The query processing algorithms that we have described so far focus on minimizing I/O cost. In this section, we discuss extensions to the query processing techniques that

help minimize memory access costs by using cache-conscious query processing algorithms and query compilation. We then discuss query processing with column-oriented storage. The algorithms we describe in this section give significant benefits for memory resident data; they are also very useful with disk-resident data, since they can speed up processing once data has been brought into the in-memory buffer.

15.8.1 Cache-Conscious Algorithms

When data is resident in memory, access is much faster than if data were resident on magnetic disks, or even SSDs. However, it must be kept in mind that data already in CPU cache can be accessed as much as 100 times faster than data in memory. Modern CPUs have several levels of cache. Commonly used CPUs today have an L1 cache of size around 64 kilobytes, with a latency of about 1 nanosecond, an L2 cache of size around 256 kilobytes, with a latency of around 5 nanoseconds, and an L3 cache of having a size of around 10 megabytes, with a latency of 10 to 15 nanoseconds. In contrast, reading data in memory results in a latency of around 50 to 100 nanoseconds. For simplicity in the rest of this section we ignore the difference between the L1, L2 and L3 cache levels, and assume that there is only a single cache level.

As we saw in Section 14.4.7, the speed difference between cache memory and main memory, and the fact that data are transferred between main memory and cache in units of a *cache-line* (typically about 64 bytes), results in a situation where the relationship between cache and main memory is not dissimilar to the relationship between main memory and disk (although with smaller speed differences). But there is a difference: while the contents of the main memory buffers disk-based data are controlled by the database system, CPU cache is controlled by the algorithms built into the computer hardware. Thus, the database system cannot directly control what is kept in cache.

However, query processing algorithms can be designed in a way that makes the best use of cache, to optimize performance. Here are some ways this can be done:

- To sort a relation that is in-memory, we use the external merge-sort algorithm, with the run size chosen such that the run fits into the cache; assuming we focus on the L3 cache, each run should be a few megabytes in size. We then use an in-memory sorting algorithm on each run; since the run fits in cache, cache misses are likely to be minimal when the run is sorted. The sorted runs (all of which are in memory) are then merged. Merging is cache efficient, since access to the runs is sequential: when a particular word is accessed from memory, the cache line that is fetched will contain the words that would be accessed next from that run.

To sort a relation larger than memory, we can use external sort-merge with much larger run sizes, but use the in-memory merge-sort technique we just described to perform the in-memory sort of the large runs.

- Hash-join requires probing of an index on the build relation. If the build relation fits in memory, an index could be built on the whole relation; however, cache hits during probe can be maximized by partitioning the relations into smaller pieces

such that each partition of the build-relation along with the index fits in the cache. Each partition is processed separately, with a build and a probe phase; since the build partition and its index fit in cache, cache misses are minimized during the build as well as the probe phase.

For relations larger than memory, the first stage of hash-join should partition the two relations such that for each partition, the partitions of the two relations together fit in memory. The technique just described can then be used to perform the hash join on each of these partitions, after fetching the contents into memory.

- Attributes in a tuple can be arranged such that attributes that tend to be accessed together are laid out consecutively. For example, if a relation is often used for aggregation, those attributes used as group by attributes, and those that are aggregated upon, can be stored consecutively. As a result, if there is a cache miss on one attribute, the cache line that is fetched would contain attributes that are likely to be used immediately.

Cache-aware algorithms are of increasing importance in modern database systems, since memory sizes are often large enough that much of the data is memory-resident.

In cases where the requisite data item is not in cache, there is a processing **stall** while the data item is retrieved from memory and loaded into cache. In order to continue to make use of the core that made the request resulting in the stall, the operating system maintains multiple threads of execution on which a core may work. Parallel query processing algorithms, which we study in Chapter 22 can use multiple threads running on a single CPU core; if one thread is stalled, another can start execution so the CPU core is utilized better.

15.8.2 Query Compilation

With data resident in memory, CPU cost becomes the bottleneck, and minimizing CPU cost can give significant benefits. Traditional databases query processors act as interpreters that execute a query plan. However, there is a significant overhead due to interpretation: for example, to access an attribute of a record, the query execution engine may repeatedly look up the relation meta-data to find the offset of the attribute within the record, since the same code must work for all relations. There is also significant overhead due to function calls that are performed for each record processed by an operation.

To avoid overhead due to interpretation, modern main-memory databases compile query plans into machine code or intermediate level byte-code. For example, the compiler can compute the offset of an attribute at compile time, and generate code where the offset is a constant. The compiler can also combine the code for multiple functions in a way that minimizes function calls. With these, and other related optimizations, compiled code has been found to execute faster, by up to a factor of 10, than interpreted code.

15.8.3 Column-Oriented Storage

In Section 13.6, we saw that in data-analytic applications, only a few attributes of a large schema may be needed, and that in such cases, storing a relation by column instead of by row may be advantageous. Selection operations on a single attribute (or small number of attributes) have significantly lower cost in a column store since only the relevant attributes need to be accessed. However, since accessing each attribute requires its own data access, the cost of retrieving many attributes is higher and may incur additional seeks if data are stored on disk.

Because column stores permit efficient access to many values for a given attribute at once, they are well suited to exploit the vector-processing capabilities of modern processors. This capability allows certain operations (such as comparisons and aggregations) to be performed in a parallel on multiple attribute values. When compiling query plans to machine code, the compiler can generate vector-processing instructions supported by the processor.

15.9 Summary

- The first action that the system must perform on a query is to translate the query into its internal form, which (for relational database systems) is usually based on the relational algebra. In the process of generating the internal form of the query, the parser checks the syntax of the user's query, verifies that the relation names appearing in the query are names of relations in the database, and so on. If the query was expressed in terms of a view, the parser replaces all references to the view name with the relational-algebra expression to compute the view.
- Given a query, there are generally a variety of methods for computing the answer. It is the responsibility of the query optimizer to transform the query as entered by the user into an equivalent query that can be computed more efficiently. Chapter 16 covers query optimization.
- We can process simple selection operations by performing a linear scan or by making use of indices. We can handle complex selections by computing unions and intersections of the results of simple selections.
- We can sort relations larger than memory by the external sort-merge algorithm.
- Queries involving a natural join may be processed in several ways, depending on the availability of indices and the form of physical storage for the relations.
 - If the join result is almost as large as the Cartesian product of the two relations, a *block nested-loop* join strategy may be advantageous.
 - If indices are available, the *indexed nested-loop* join can be used.

- If the relations are sorted, a *merge join* may be desirable. It may be advantageous to sort a relation prior to join computation (so as to allow use of the merge-join strategy).
- The *hash-join* algorithm partitions the relations into several pieces, such that each piece of one of the relations fits in memory. The partitioning is carried out with a hash function on the join attributes so that corresponding pairs of partitions can be joined independently.
- Duplicate elimination, projection, set operations (union, intersection, and difference), and aggregation can be done by sorting or by hashing.
- Outer-join operations can be implemented by simple extensions of join algorithms.
- Hashing and sorting are dual, in the sense that any operation such as duplicate elimination, projection, aggregation, join, and outer join that can be implemented by hashing can also be implemented by sorting, and vice versa; that is, any operation that can be implemented by sorting can also be implemented by hashing.
- An expression can be evaluated by means of materialization, where the system computes the result of each subexpression and stores it on disk and then uses it to compute the result of the parent expression.
- Pipelining helps to avoid writing the results of many subexpressions to disk by using the results in the parent expression even as they are being generated.

Review Terms

- | | |
|----------------------------|-------------------------------|
| • Query processing | • Disjunctive selection |
| • Evaluation primitive | • Composite index |
| • Query-execution plan | • Intersection of identifiers |
| • Query-evaluation plan | • External sorting |
| • Query-execution engine | • External sort-merge |
| • Measures of query cost | • Runs |
| • Sequential I/O | • <i>N</i> -way merge |
| • Random I/O | • Equi-join |
| • File scan | • Nested-loop join |
| • Linear search | • Block nested-loop join |
| • Selections using indices | • Indexed nested-loop join |
| • Access paths | • Merge join |
| • Index scans | • Sort-merge join |
| • Conjunctive selection | • Hybrid merge join |

- Hash-join
 - Build
 - Probe
 - Build input
 - Probe input
 - Recursive partitioning
 - Hash-table overflow
 - Skew
 - Fudge factor
 - Overflow resolution
 - Overflow avoidance
- Hybrid hash-join
- Spatial join
- Operator tree
- Materialized evaluation
- Double buffering
- Pipelined evaluation
 - Demand-driven pipeline (lazy, pulling)
 - Producer-driven pipeline (eager, pushing)
 - Iterator
 - Pipeline stages
- Double-pipelined join
- Continuous query evaluation

Practice Exercises

- 15.1** Assume (for simplicity in this exercise) that only one tuple fits in a block and memory holds at most three blocks. Show the runs created on each pass of the sort-merge algorithm when applied to sort the following tuples on the first attribute: (kangaroo, 17), (wallaby, 21), (emu, 1), (wombat, 13), (platypus, 3), (lion, 8), (warthog, 4), (zebra, 11), (meerkat, 6), (hyena, 9), (hornbill, 2), (baboon, 12).
- 15.2** Consider the bank database of Figure 15.14, where the primary keys are underlined, and the following SQL query:

```
select T.branch_name
from branch T, branch S
where T.assets > S.assets and S.branch_city = "Brooklyn"
```

Write an efficient relational-algebra expression that is equivalent to this query. Justify your choice.

- 15.3** Let relations $r_1(A, B, C)$ and $r_2(C, D, E)$ have the following properties: r_1 has 20,000 tuples, r_2 has 45,000 tuples, 25 tuples of r_1 fit on one block, and 30 tuples of r_2 fit on one block. Estimate the number of block transfers and seeks required using each of the following join strategies for $r_1 \bowtie r_2$:
- a. Nested-loop join.
 - b. Block nested-loop join.

- c. Merge join.
 - d. Hash join.
- 15.4** The indexed nested-loop join algorithm described in Section 15.5.3 can be inefficient if the index is a secondary index and there are multiple tuples with the same value for the join attributes. Why is it inefficient? Describe a way, using sorting, to reduce the cost of retrieving tuples of the inner relation. Under what conditions would this algorithm be more efficient than hybrid merge join?
- 15.5** Let r and s be relations with no indices, and assume that the relations are not sorted. Assuming infinite memory, what is the lowest-cost way (in terms of I/O operations) to compute $r \bowtie s$? What is the amount of memory required for this algorithm?
- 15.6** Consider the bank database of Figure 15.14, where the primary keys are underlined. Suppose that a B⁺-tree index on *branch_city* is available on relation *branch*, and that no other index is available. List different ways to handle the following selections that involve negation:
- a. $\sigma_{\neg(\text{branch_city} < \text{"Brooklyn"})}(\text{branch})$
 - b. $\sigma_{\neg(\text{branch_city} = \text{"Brooklyn"})}(\text{branch})$
 - c. $\sigma_{\neg(\text{branch_city} < \text{"Brooklyn"} \vee \text{assets} < 5000)}(\text{branch})$
- 15.7** Write pseudocode for an iterator that implements indexed nested-loop join, where the outer relation is pipelined. Your pseudocode must define the standard iterator functions *open()*, *next()*, and *close()*. Show what state information the iterator must maintain between calls.
- 15.8** Design sort-based and hash-based algorithms for computing the relational division operation (see Practice Exercise 2.9 for a definition of the division operation).

```

branch(branch_name, branch_city, assets)
customer(customer_name, customer_street, customer_city)
loan(loan_number, branch_name, amount)
borrower(customer_name, loan_number)
account(account_number, branch_name, balance)
depositor(customer_name, account_number)

```

Figure 15.14 Bank database.

- 15.9** What is the effect on the cost of merging runs if the number of buffer blocks per run is increased while overall memory available for buffering runs remains fixed?
- 15.10** Consider the following extended relational-algebra operators. Describe how to implement each operation using sorting and using hashing.
- a. **Semijoin** (\bowtie_{θ}): The multiset semijoin operator $r \bowtie_{\theta} s$ is defined as follows: if a tuple r_i appears n times in r , it appears n times in the result of $r \bowtie_{\theta}$ if there is at least one tuple s_j such that r_i and s_j satisfy predicate θ ; otherwise r_i does not appear in the result.
 - b. **Anti-semijoin** ($\overline{\bowtie}_{\theta}$): The multiset anti-semijoin operator $r \overline{\bowtie}_{\theta} s$ is defined as follows: if a tuple r_i appears n times in r , it appears n times in the result of $r \overline{\bowtie}_{\theta}$ if there does not exist any tuple s_j in s such that r_i and s_j satisfy predicate θ ; otherwise r_i does not appear in the result.
- 15.11** Suppose a query retrieves only the first K results of an operation and terminates after that. Which choice of demand-driven or producer-driven pipelining (with buffering) would be a good choice for such a query? Explain your answer.
- 15.12** Current generation CPUs include an *instruction cache*, which caches recently used instructions. A function call then has a significant overhead because the set of instructions being executed changes, resulting in cache misses on the instruction cache.
- a. Explain why producer-driven pipelining with buffering is likely to result in a better instruction cache hit rate, as compared to demand-driven pipelining.
 - b. Explain why modifying demand-driven pipelining by generating multiple results on one call to *next()*, and returning them together, can improve the instruction cache hit rate.
- 15.13** Suppose you want to find documents that contain at least k of a given set of n keywords. Suppose also you have a keyword index that gives you a (sorted) list of identifiers of documents that contain a specified keyword. Give an efficient algorithm to find the desired set of documents.
- 15.14** Suggest how a document containing a word (such as “leopard”) can be indexed such that it is efficiently retrieved by queries using a more general concept (such as “carnivore” or “mammal”). You can assume that the concept hierarchy is not very deep, so each concept has only a few generalizations (a concept can, however, have a large number of specializations). You can also assume that you are provided with a function that returns the concept for each word in a document. Also suggest how a query using a specialized concept can retrieve documents using a more general concept.

- 15.15** Explain why the nested-loops join algorithm (see Section 15.5.1) would work poorly on a database stored in a column-oriented manner. Describe an alternative algorithm that would work better, and explain why your solution is better.
- 15.16** Consider the following queries. For each query, indicate if column-oriented storage is likely to be beneficial or not, and explain why.
- Fetch ID, *name* and *dept_name* of the student with ID 12345.
 - Group the *takes* relation by *year* and *course_id*, and find the total number of students for each (*year*, *course_id*) combination.

Exercises

- 15.17** Suppose you need to sort a relation of 40 gigabytes, with 4-kilobyte blocks, using a memory size of 40 megabytes. Suppose the cost of a seek is 5 milliseconds, while the disk transfer rate is 40 megabytes per second.
- Find the cost of sorting the relation, in seconds, with $b_b = 1$ and with $b_b = 100$.
 - In each case, how many merge passes are required?
 - Suppose a flash storage device is used instead of a disk, and it has a latency of 20 microseconds and a transfer rate of 400 megabytes per second. Recompute the cost of sorting the relation, in seconds, with $b_b = 1$ and with $b_b = 100$, in this setting.
- 15.18** Why is it not desirable to force users to make an explicit choice of a query-processing strategy? Are there cases in which it *is* desirable for users to be aware of the costs of competing query-processing strategies? Explain your answer.
- 15.19** Design a variant of the hybrid merge-join algorithm for the case where both relations are not physically sorted, but both have a sorted secondary index on the join attributes.
- 15.20** Estimate the number of block transfers and seeks required by your solution to Exercise 15.19 for $r_1 \bowtie r_2$, where r_1 and r_2 are as defined in Exercise 15.3.
- 15.21** The hash-join algorithm as described in Section 15.5.5 computes the natural join of two relations. Describe how to extend the hash-join algorithm to compute the natural left outer join, the natural right outer join, and the natural full outer join. (Hint: Keep extra information with each tuple in the hash index to detect whether any tuple in the probe relation matches the tuple in the hash index.) Try out your algorithm on the *takes* and *student* relations.

- 15.22** Suppose you have to compute $_{A}Y_{sum(C)}(r)$ as well as $_{A,B}Y_{sum(C)}(r)$. Describe how to compute these together using a single sorting of r .
- 15.23** Write pseudocode for an iterator that implements a version of the sort – merge algorithm where the result of the final merge is pipelined to its consumers. Your pseudocode must define the standard iterator functions *open()*, *next()*, and *close()*. Show what state information the iterator must maintain between calls.
- 15.24** Explain how to split the hybrid hash-join operator into sub-operators to model pipelining. Also explain how this split is different from the split for a hash-join operator.
- 15.25** Suppose you need to sort relation r using sort–merge and merge–join the result with an already sorted relation s .
- Describe how the sort operator is broken into suboperators to model the pipelining in this case.
 - The same idea is applicable even if both inputs to the merge join are the outputs of sort–merge operations. However, the available memory has to be shared between the two merge operations (the merge–join algorithm itself needs very little memory). What is the effect of having to share memory on the cost of each sort-merge operation?

Further Reading

[Graefe (1993)] presents an excellent survey of query-evaluation techniques. [Faerber et al. (2017)] describe main-memory database implementation techniques, including query processing techniques for main-memory databases, while [Kemper et al. (2012)] describes techniques for query processing with in-memory columnar data. [Samet (2006)] provides a textbook description of spatial data structures, while [Shekhar and Chawla (2003)] provides a textbook description of spatial databases, including indexing and query processing techniques. Textbook descriptions of techniques for indexing documents, and efficiently computing ranked answers to keyword queries may be found in [Manning et al. (2008)].

Bibliography

- [Faerber et al. (2017)] F. Faerber, A. Kemper, P.-A. Larson, J. Levandoski, T. Neumann, and A. Pavlo, “Main Memory Database Systems”, *Foundations and Trends in Databases*, Volume 8, Number 1-2 (2017), pages 1–130.
- [Graefe (1993)] G. Graefe, “Query Evaluation Techniques for Large Databases”, *ACM Computing Surveys*, Volume 25, Number 2 (1993).

- [Kemper et al. (2012)] A. Kemper, T. Neumann, F. Funke, V. Leis, and H. Mühe, “HyPer: Adapting Columnar Main-Memory Data Management for Transaction AND Query Processing”, *IEEE Data Engineering Bulletin*, Volume 35, Number 1 (2012), pages 46–51.
- [Manning et al. (2008)] C. D. Manning, P. Raghavan, and H. Schütze, *Introduction to Information Retrieval*, Cambridge University Press (2008).
- [Samet (2006)] H. Samet, *Foundations of Multidimensional and Metric Data Structures*, Morgan Kaufmann (2006).
- [Shekhar and Chawla (2003)] S. Shekhar and S. Chawla, *Spatial Databases: A TOUR*, Pearson (2003).

Credits

The photo of the sailboats in the beginning of the chapter is due to ©Pavel Nesvadba/Shutterstock.